

PRODUCT DATASHEET

LED Spot Pear 1 x 4.3W 2700K GU10

LED Spot Pear Grey | Ceiling mounted luminaires with adjustable GU10 spotlights



Areas of application

- Indoor applications

Product benefits

- Osram lamp included

Product features

- GU10 lamp included
- Housing material: Plastic and Metal
- Adjustable head



TECHNICAL DATA

Electrical data


| | |
|---|---------------|
| Nominal wattage | 4.30 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 38.000 mA |
| Inrush current | 3 A |
| Inrush current time T_{h50} | 500 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 53 |
| Max. number of luminaires per miniature circuit breaker C10 | 53 |
| Max. number of luminaires per miniature circuit breaker C16 | 85 |
| Power factor λ | > 0.5 |
| Protection class | I |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|---------------------|
| Luminous flux | 210 lm |
| Total luminous flux of contained light sources | 350 lm |
| Luminous efficacy | 48 lm/W |
| Color temperature | 2700 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | ≥80 |
| Standard deviation of color matching | ≤6 sdc _m |
| Luminous intensity | 600 |
| Flickering metric (Pst LM) | ≤1 |
| Stroboscope effect metric (SVM) | ≤0.4 |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 36 ° |
| UGR | < 25 |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 80.00 mm |
| Width | 110.00 mm |
| Height | 92.00 mm |
| Product weight | 220.00 g |



LED SPOT PEAR 1X4.3W 827
GU10

Materials & Colors

| | |
|--|---------------|
| Product color | Gray |
| Housing color | Gray |
| Body material | Plastic METAL |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|--|------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Screw terminal, 3-Pole |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK06 |
| Dimmable | No |
| Mounting type | Surface |
| With light source | Yes |
| Replaceable light source | No |
| Holder designation | GU10 |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
| Number of switching cycles | 100000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| | |
|--|-----------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |

Additional product data

| | |
|----------------|-------------------------------|
| Product remark | Maximum bulb wattage: 5 W LED |
|----------------|-------------------------------|

Number of illuminants

1




EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|----------------------------|
|  | User instruction / safety instructions | UI LED SPOT PEAR |
|  | Declarations of conformity | CE Declaration Spot Pear |
|  | Declarations of conformity UKCA | UKCA Declaration Spot Pear |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075826496 | Folding box 1 | 100 mm x 110 mm x 142 mm | 293.00 g | 1.56 dm ³ |
| 4058075826502 | Shipping box 6 | 318 mm x 238 mm x 170 mm | 2128.00 g | 12.87 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.