

# PRODUCT DATASHEET LDVAL SECURITY FLOOD 2X10W TRI MS

VALUE CLASS

LED VALUE SECURITY FLOODLIGHT | IP65 security floodlight with TRI CCT in single or double adjustable head



#### Areas of application

- Outdoor use (IP65)
- Building facades

# Product benefits

- Available in TRI CCT as a single or double adjustable head
- Motion sensor versions available, providing additional security and safety
- Large terminal block for simple installation

#### Product features

- Type of protection: IP65
- TRI colour 3000K, 4000K and 6500K via dip switch
- $-\,$  High luminous efficacy: up to 100 lm/W
- Ambient temperature in operation: -20...+50 °C
- Long lifetime: up to 30,000 h
- 5 years warranty



## **TECHNICAL DATA**

#### Electrical data

Nominal wattage	2x10 W
Nominal voltage	220240 V
Power factor λ	> 0.5

## Photometrical data

Luminous flux	1800 2000 lm	
Luminous efficacy	900 lm/W	
Color temperature	3000 K / 4000 K / 6500 K	
Light color (designation)	Warm White / Cool White / Cool Daylight	
Color rendering index Ra	≥80	
Standard deviation of color matching	< 6 sdcm	
Beam angle	100 °	

# Dimensions & Weight

Length	290.00 mm
Width	132.00 mm
Height	170.00 mm
Product weight	700.00 g

## Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polycarbonate (PC)

# Application & Mounting

Ambient temperature range	-20+50 °C
Type of connection	Screw terminal, 3-Pole
Type of protection	IP54
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling / Wall
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	30000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	30000 h

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Sensor

Type of sensor	PIR

#### Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

# Additional product data

Number of illuminants	2
-----------------------	---

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075542303	Folding box 1			
4058075542310	Shipping box 12	470 mm x 315 mm x 275 mm	9000.00 g	40.71 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.