

PRODUCT DATASHEET

LED VALUE HW 60 27 W/6500 K B22d

LED VALUE HIGH WATTAGE | LED lamps with classic bulbs, high wattage



Areas of application

- Suitable for indoor applications.
- Warehouses
- Workshops
- Stadiums
- Car parks

Product benefits

- Energy savings of up to 50 % compared to conventional compact fluorescent lamps
- Accessory cover works as a reflector and increase the illuminance up to 100 %
- Wide beam angle: 200°
- Long lifetime of up to 20,000 h
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time

Product features

- Luminous efficacy: up to 100 lm/W
- Color rendering index R_a : ≥ 80
- Power factor: 0.9
- Mercury-free lamps



TECHNICAL DATA

Electrical data

Nominal wattage	27 W
Construction wattage	27.00 W
Nominal voltage	100...240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	330 mA
Type of current	AC
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor λ	0.90

Photometrical data

Luminous flux	3105 lm
Luminous efficacy	115 lm/W
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤ 6 sdc _m

Light technical data

Beam angle	180 °
Starting time	< 0.5 s

Dimensions & Weight

Overall length	158.00 mm
Diameter	100.00 mm
Maximum diameter	100 mm
Product weight	108.00 g

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	75 °C

Lifespan

Number of switching cycles	100000
----------------------------	--------

Additional product data

Base (standard designation)	B22d
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted

Capabilities

Dimmable	No
----------	----

Certificates & Standards

Type of protection	IP20
Standards	CB / EMC / ROHS
Photobiological safety group acc. to EN62778	RG0

Country-specific categorizations

Order reference	LV HW 27W/865 1
-----------------	-----------------

LOGISTICAL DATA

Temperature range at storage	-20...+80 °C
------------------------------	--------------

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	B22d
Length	158.00 mm
Height	100.00 mm
Width	100.00 mm

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854174025	Folding box 1	102 mm x 102 mm x 165 mm	165.00 g	1.72 dm ³
4099854174032	Shipping box 10	532 mm x 227 mm x 194 mm	2134.00 g	23.43 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.