

PRODUCT DATASHEET

LN INV D 1500 P 52W 940 PS BK

LINEAR INDIVILED DIRECT 1500 PS | Surface mounted luminaire for single or light line office application with CRI90 and power select (PS) feature, 1500 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- High performance with CRI90 and up to 130 lm/W
- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Symmetric light distribution for various application areas
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)



- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)


TECHNICAL DATA

Electrical data


Nominal wattage	52 W / 48 W / 46 W / 40 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	240...220...205...185 mA
Inrush current	14.6 A
Inrush current time T_{h50}	170 μ s
Max. number of luminaires per miniature circuit breaker B16	28
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	6350 lm / 5900 lm / 5700 lm / 5050 lm
Luminous efficacy	122 lm/W / 123 lm/W / 124 lm/W / 126 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq$ 90
Standard deviation of color matching	3 sdcn
Low flicker	Yes
Flickering metric (Pst LM)	$\leq$ 1
Stroboscope effect metric (SVM)	$\leq$ 0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 °
UGR	< 19



LN INV D 1500 P 52W 940 PS BK 1050mA




LN INV D 1500 P 52W 940 PS BK

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
52 W	4000 K	6350 lm	122 lm/W
48 W	4000 K	5900 lm	123 lm/W
46 W	4000 K	5700 lm	124 lm/W
40 W	4000 K	5050 lm	126 lm/W

Dimensions & Weight

Length	1475.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3900.00 g



LN INV 1500 P

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
---------------------------	------------------------

Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1050mA / 975mA / 900mA / 800 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM OT FIT 55/220–240/1A0 CS L AP

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00027-V01.01-EN
Replaceable light source (EPREL)	By the end consumer

Additional product data

Number of illuminants	1
Added function	EVERLOOP / MULTI SELECT

Accessories Optional

Product image	Product name	EAN
	LN INV SUSPENSION KIT BK	4099854297069
	LN INV SUSPENSION WIRE	4099854323980
	LN INV 1500 THROUGHWIRING KIT	4099854214806

Product image	Product name	EAN
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR BK	4099854308079
	LN INV INFILL 600 BK	4099854297045
	LN INV INFILL 1200 BK	4099854297007
	LN INV INFILL 1500 BK	4099854297021

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	LN INV
 Legal information	Safety Insert G11205497

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Legal Insert G11235609
	Legal information	LN INV D DI
	Declarations of conformity	LN INV
	Declarations of conformity UKCA	LN INV
	Certificates	LN INV
Photometric and lighting design files		Document name
	IES file (IES)	LN INV D 1500 P 52W 940 PS BK 1050mA
	LDT file (Eulumdat)	LN INV D 1500 P 52W 940 PS BK 1050mA
	ULD file (DIALux)	LN INV D 1500 P 52W 940 PS BK
	ROLF file (RELUX)	LN INV D 1500 P 52W 940 PS BK
	UGR file (UGR table)	LN INV D 1500 P 52W 940 PS BK 1050mA
	Light distribution curve type cone	LN INV D 1500 P 52W 940 PS BK 1050mA
	Light distribution curve type polar	LN INV D 1500 P 52W 940 PS BK
CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D 1500 G2
Tender texts		Document name
	Tender documents	LINEAR INDIVILED DIRECT 1500 PS P 52W 940 PS BK-EN


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854296826	Folding box 1	177 mm x 1,530 mm x 102 mm	4600.00 g	27.62 dm ³
4099854296833	Shipping box 2	1,550 mm x 197 mm x 224 mm	10800.00 g	68.40 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

LINEAR InduLED® DIRECT BK	DIRECT	LED module		NA	W	H	BxW
		Part 1	Part 2				
LN INV D 1500 P 40W 940 PS BK	COMPACT	QFP	+	500	30	4000	1007
	QFP	CM	-	500	30	3999	100
	CM	QFP	+	500	30	4000	100
LN INV D 1500 P 40W 940 PS BK	CM	CM	Thru-hole	500	30	4000	1007
	QFP	QFP	+	500	30	3999	100
	QFP	CM	-	500	30	3999	100
LN INV D 1500 P 40W 940 PS BK	CM	QFP	+	500	30	4000	1007
	QFP	CM	-	500	30	3999	100
	CM	QFP	+	500	30	4000	100
LN INV D 1500 P 52W 940 PS BK	COMPACT	QFP	+	500	30	4000	1007
	QFP	CM	-	500	30	3999	100
	CM	QFP	+	500	30	4000	100
LN INV D 1500 P 52W 940 PS BK	CM	CM	Thru-hole	500	30	4000	1007
	QFP	QFP	+	500	30	3999	100
	QFP	CM	-	500	30	3999	100
LN INV D 1500 P 52W 940 PS BK	CM	QFP	+	500	30	4000	1007
	QFP	CM	-	500	30	3999	100
	CM	QFP	+	500	30	4000	100



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.