

PRODUCT DATASHEET

LN INV DI 1200 P 54W 930 DAVR WT

LINEAR INDIVILED DIRECT/INDIRECT 1200 DALI | Pendant luminaire for single or light line office application with CRI90 and DALI-2 IoT technology, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct and indirect lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- Homogenous light distribution and reduced glare ($UGR \leq 19$) thanks to IndiviLED® optics
- Pendant luminaires with direct light emission (70%) and indirect light emission (30%)
- High performance with CRI90 and up to 137 lm/W
- IoT-ready luminaire with DALI-2 driver, suitable for VIVARES and other Light Management Systems
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Suitable for battery emergency installations acc. to EN 60598-2-22
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color



- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)
- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)
- Multi lumen function: programmable DALI-2 driver


TECHNICAL DATA

Electrical data


Nominal wattage	54 W / 48 W / 43 W / 34 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	233...205...195...160 mA
Inrush current	25.2 A
Inrush current time T_{h50}	40 μ s
Max. number of luminaires per miniature circuit breaker B16	29
Max. number of luminaires per miniature circuit breaker C10	23
Max. number of luminaires per miniature circuit breaker C16	38
Power factor λ	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Operating mode	Integrated LED driver
Dimming interface	DALI-2 / IoT

Photometrical data

Luminous flux	6500 lm / 5750 lm / 5200 lm / 4350 lm
Luminous efficacy	120 lm/W / 121 lm/W / 128 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	$\geq$ 90
Standard deviation of color matching	3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	$\leq$ 1
Stroboscope effect metric (SVM)	$\leq$ 0.4
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	90 ° + 130 °
UGR	< 19



LN INV DI 1200 P 54W 930 DAVR WT 1100mA




LN INV DI 1200 P 54W 930 DAVR WT

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
54 W	3000 K	6500 lm	120 lm/W
48 W	3000 K	5750 lm	120 lm/W
43 W	3000 K	5200 lm	121 lm/W
34 W	3000 K	4350 lm	128 lm/W

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3540.00 g



LN INV 1200 P

Materials & Colors

Product color	White
Housing color	White
RAL Color (most similar)	RAL 9003
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Type of dimming	DALI2
IoT ready	Support of DALI data type PART 251, 252, 253 ¹⁾
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	Yes

1) Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	1100mA / 950mA / 850mA / 700 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM type OTI DALI 50/220-240/1A4 NFC L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
EPD	LEDV-00026-V01.01-EN
Replaceable light source (EPREL)	By the end consumer

Additional product data

Number of illuminants	2
Added function	EVERLOOP / VIVARES / Programmable Multi Lumen

Accessories Mandatory

Product image	Product name	EAN
	LN INV SUSPENSION KIT WT	4099854215537
	LN INV SUSPENSION WIRE	4099854323980

Accessories Optional

Product image	Product name	EAN
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR WT	4099854308093
	LN INV INFILL 600 WT	4099854214882
	LN INV INFILL 1200 WT	4099854214868
	LN INV INFILL 1500 WT	4099854214844

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Upgrade and replacement components

Components Light Source		
Product image	Product name	EAN
	LISOEV 1074x29 48 40W 930 S90U19 GY	4099854284359

Product image	Product name	EAN
	LISOEV 1200x31 22 18W 930 S130	4099854284939

Components Driver

Product image	Product name	EAN
	OTi DALI 50/220...240/1A4 NFC L	4062172074988

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	LN INV D PS
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11205497
	Legal information	Legal Insert G11235610
	Legal information	LN INV D DI
	Declarations of conformity	LN INV
	Declarations of conformity UKCA	LN INV
	EU Data Act	DALI LED Driver and Luminaires


Documents and certificates		Document name
	EPD	EPD EN LINEAR INDIVILED DIRECT INDIRECT
Photometric and lighting design files		Document name
	IES file (IES)	LN INV DI 1200 P 54W 930 DAVR WT 1100mA
	LDT file (Eulumdat)	LN INV DI 1200 P 54W 930 DAVR WT 1100mA
	ULD file (DIALux)	LN INV DI 1200 P 54W 930 DAVR WT
	ROLF file (RELUX)	LN INV DI 1200 P 54W 930 DAVR WT
	UGR file (UGR table)	LN INV DI 1200 P 54W 930 DAVR WT 1100mA
	Light distribution curve type cone	LN INV DI 1200 P 54W 930 DAVR WT 1100mA
	Light distribution curve type polar	LN INV DI 1200 P 54W 930 DAVR WT
CAD/BIM files		Document name
	BIM Revit 3D	Linear Indiviled G2
	CAD STEP 3D	LN INV D I 1200 G2
Tender texts	Document name	
	Tender documents	LINEAR INDIVILED DIRECTINDIRECT 1200 DALI 1200 P 54W 930 DAVR WT-EN

LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854135552	Folding box 1	178 mm x 1,263 mm x 103 mm	4140.00 g	23.16 dm³
4099854135569	Shipping box 2	1,277 mm x 187 mm x 189 mm	9680.00 g	45.13 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



LINEAR INDETERMINED DRIVING DATA SET	DRIVER	DIRECT				INDIRECT				Total	acc	DMS magn
		acc	br	br	br	acc	br	br	br			
LN INV 1200 P 300W 3400 CLARK WIT	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
LN INV 1200 P 300W 3400 CLARK WIT	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
LN INV 1200 P 300W 3400 CLARK WIT	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
LN INV 1200 P 300W 3400 CLARK WIT	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28
	OTI DALE BU	27	28	28	28	27	28	28	28	27	28	28



– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.