

PRODUCT DATASHEET LED TUBE T8 EM ENERGY EFFICIENCY CLASS A 1200 mm 10W 840

LED TUBE T8 EM ENERGY EFFICIENCY CLASS A | High performance LED tubes for electromagnetic control gear (CCG) and AC mains, EEC A



Areas of application

- General illumination within ambient temperatures from -20...+50 $^{\circ}\text{C}$
- Illumination of production areas
- Traffic zones and corridors
- Supermarkets and department stores
- Industry

Product benefits

- Highest energy savings possible thanks to energy efficiency class A
- No bending thanks to glass technology
- Very high resistance to switching loads
- Quick, simple and safe replacement without rewiring
- Energy savings of up to 72 % (compared to T8 fluorescent lamp)
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Also suitable for operation at low temperatures

Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires or on AC mains
- Extremly high efficiency of 210 lm/W
- Low flicker according to EU 2019-2020 (SVM ≤ 0.4 / PstLM ≤ 1)





- ENEC 10 VDE mark
- Lifetime up to 100,000 h
- Type of protection: IP20
- Mercury-free and RoHS compliant

TECHNICAL DATA

Electrical data


Nominal wattage	10 W
Construction wattage	10.00 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Nominal current	47 mA
Type of current	AC
Inrush current	3 A
Suitable for DC input	Yes
Input voltage DC	186260 V
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz ¹⁾
Max. lamp number on MCB B10 A	85
Max. lamp number on MCB B10 A - CCG without compensation	85
Max. lamp number on MCB B10 A - CCG with compensation	14
Max. lamp number on MCB B16 A	125
Max. lamp number on MCB B16 A - CCG without compensation	125
Max. lamp number on MCB B16 A - CCG with compensation	22
Total harmonic distortion	22 %
Power factor λ	0.90

¹⁾ DC 0Hz

Photometrical data

Luminous flux	2100 lm
Luminous efficacy	210 lm/W
Lumen main.fact.at end of nom.life time	0.96
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1

Stroboscope effect metric (SVM)	0,4
---------------------------------	-----



EPREL data spectral diagram PROF LEDr 4000K

Light technical data

Beam angle	190 °	
Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

Dimensions & Weight



Overall length	1212.00 mm
Length with base excl. base pins/connection	1200.00 mm
Diameter	26.70 mm
Product weight	234.00 g

Temperatures & operating conditions

Ambient temperature range	-20+50 °C ¹⁾
Maximum temperature at tc test point	75 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	100000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.96

November 21, 2025, 18:13:00 LED TUBE T8 EM ENERGY EFFICIENCY CLASS A 1200 mm 10W 840

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	A 1)
Energy consumption	10.00 kWh/1000h
Type of protection	IP20
	CE / UKCA / VDE / ENEC / EAC
Standards	
Standards Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations	RG0 west efficiency)
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lover the content of the content o	
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations	west efficiency)
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference	west efficiency)
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA	west efficiency) LEDTUBE T8 EM E
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage	west efficiency) LEDTUBE T8 EM E
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015	west efficiency) LEDTUBE T8 EM E -20+80 °C
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used	LEDTUBE T8 EM E -20+80 °C
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional	LEDTUBE T8 EM E -20+80 °C LED NDLS
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains	LEDTUBE T8 EM E -20+80 °C LED NDLS MLS
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface)	LEDTUBE T8 EM E -20+80 °C LED NDLS MLS G13
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS)	LEDTUBE T8 EM E -20+80 °C LED NDLS MLS G13 No
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source	LEDTUBE T8 EM E -20+80 °C LED NDLS MLS G13 No No
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope	west efficiency) LEDTUBE T8 EM E -20+80 °C LED NDLS MLS G13 No No No No
Photobiological safety group acc. to EN62778 1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (low Country-specific categorizations Order reference LOGISTICAL DATA Temperature range at storage Energy labelling regulation data acc EU 2019/2015 Lighting technology used Non-directional or directional Mains or non-mains Light source cap-type (or other electric interface) Connected light source (CLS) Color-tuneable light source Envelope High luminance light source	west efficiency) LEDTUBE T8 EM E -20+80 °C LED NDLS MLS G13 No No No No No

No

Claim of equivalent power

Length	1212.00 mm
Height	26.70 mm
Width	26.70 mm
Chromaticity coordinate x	0,3818
Chromaticity coordinate y	0,3797
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	1791819
Model number	AC57040,AC57040

EQUIPMENT / ACCESSORIES

- Suitable for operation with low-loss and conventional control gears

Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Not suitable for emergency lighting.
- Disconnect mains before installation.

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LEDTUBE T8 EM EECA	
PDF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN	
PDF	Extended installation guide	Notes on the operation of LEDVANCE LED tubes in compensated luminaires	
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF	Declarations of conformity	LEDTUBE T8 EM EECA	

	Documents and certificates	S	Document name
PDF	Declarations of conformity	UKCA	LEDTUBE T8 EM EECA
	Photometric and lighting de	esign files	Document name
	IES file (IES)		LEDTUBE T8 EM EECA S 1200 10W 840
	LDT file (Eulumdat)		LEDTUBE T8 EM EECA S 1200 10W 840
	UGR file (UGR table)		LEDTUBE T8 EM EECA S 1200 10W 840
	Light distribution curve type polar		LEDTUBE T8 EM EECA S 1200 10W 840
	Spectral power distribution	1	EPREL data spectral diagram PROF LEDr 4000K
	Tender texts	Document nar	me
	Tender documents	LED TUBE T8 EM ENERGY EFFICIENCY CLASS A S 1200 mm 10W 840-EN	
	Tender texts	Document nar	me

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854223310	Sleeve 1	1,255 mm x 29 mm x 29 mm	263.00 g	1.06 dm ³
4099854223327	Shipping box 10	1,290 mm x 170 mm x 95 mm	3246.00 g	20.83 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.