

# PRODUCT DATASHEET

## LHT-HV 20K F2



### Areas of application

- Residential installations

### Product benefits

- 10 years of product guarantee
- Compatible with many energy storage systems manufacturers
- Possible selection of different work modes
- Inverter is powered by the grid or the battery and is independent of the PV panels
- Bluetooth connection possible
- Charge / discharge of the energy storage system is faster than with LV version
- AFCI protection, proactively reduces fire risk

### Product features

- 1 battery input
- Cooling by natural convection
- Protection rating: IP66
- Original Stäubli MC4 connectors
- Up to 50 A of charging/discharging current
- UPS level switching time (< 10 ms) supporting critical loads all the time

## TECHNICAL DATA

## Electrical data

Output phases	3-phase
Max. input power DC	32 kW
Input voltage DC	600 V
MPP voltage	200-850 V
Max. input current DC	20 A
Max. input current DC per string input	20 A
Max. input current DC per MPP tracker	20 A
Number of independent MPPT inputs	4
String connections per MPPT input	1
Nominal output power AC	20 kW
Power consumption	<25 W

## Dimensions &amp; Weight

Length	563 mm
Width	546 mm
Height	235 mm
Product weight	32600.00 g

## Additional product data

Integrated DC switch	Yes
Connection DC for battery	Yes
Suitable for emergency power	Yes
Charging controller integrated	Yes
With data logging	Yes
Wireless	Yes
Display	Standard
Ethernet	Yes
Integrated transformer	No
Type of connection	Staubli MC4
Temperature range in operation	-25...+60 °C
Ambient temperature range	-25...+60 °C
Outdoor application	No
Type of protection	IP66
Product color	White

## Efficiency

Maximum efficiency	98,50 %
--------------------	---------

European efficiency

97,50 %

## EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Data logger included
- AC and AC backup connector included
- Supplied with user manual
- Additional DC connectors for the outlets on the inverter
- Bluetooth antenna included
- Eastron meter and CT clamps included
- Power and communication cables for the battery system included

## DOWNLOAD DATA

Documents and certificates	Document name
 <a href="#">User instruction / safety instructions</a>	LHT-HV-12-20K F2
 <a href="#">Declarations of conformity</a>	CE Certificate LHT-HV 12-20K F2
 <a href="#">Product family datasheet</a>	LHT-HV-12-20K F2

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854438493	Shipping box 1	645 mm x 695 mm x 343 mm	33370.00 g	153.76 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## References / Links

- For Guarantee see [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.