

PRODUCT DATASHEET SURFACE MOUNT DOWNLIGHT 215 24W TRI

SURFACE MOUNT DOWNLIGHT | Downlights



Areas of application

- Public areas
- Living areas (living rooms, dining rooms, bedrooms etc.)
- Reception areas and foyers
- Entrances / Hallways
- Retail
- Hospitality

Product features

- TRI CCT (3000K/4000K/6500K)
- High luminous efficacy: 90 lm/W
- Type of protection: IP44
- Pre-wired with flex and plug
- Lifetime up to 25,000 h

TECHNICAL DATA

Electrical data

Nominal wattage	25.00 W
Protection class	П

Photometrical data

Color rendering index Ra	> 80

Dimensions & Weight

Diameter	215.00 mm
Height	39.00 mm
Product weight	281.00 g

Materials & Colors

Product color	White
Housing color	White
Body material	Plastic

Application & Mounting

Type of protection	IP44
Dimmable	No
Mounting type	Surface
Application environment	Indoor
Replaceable light source	No

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854181542	Folding box	218 mm x 47 mm x 228 mm	339.00 g	2.34 dm ³
4099854181559	Shipping box 40	500 mm x 455 mm x 485 mm	14640.00 g	110.34 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.