

PRODUCT DATASHEET FL H M POWER SUPPLY V 300W DALI

FLOODLIGHT HIGH MAST POWER SUPPLY | Floodlight High Mast power supplies



Areas of application

- Outdoor use (IP66)
- Suitable for high mast applications
- Lighting of large areas
- Construction areas
- Industry

Product benefits

- Highly robust and durable
- Optimized product logistic, luminaire heads and power supplies to be ordered separately in stand-alone packaging
- 5 years guarantee

Product features

- Power supply for floodlight high mast luminaire heads
- Joint or separate installation with floodlight high mast power supply
- M16 cable gland for mains cable


TECHNICAL DATA

Electrical data

Nominal wattage	300.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Power factor λ	> 0.90	
Total harmonic distortion	< 15 %	
Protection class	1	

Dimensions & Weight

Length	317.00 mm
Width	201.00 mm
Height	61.00 mm
Product weight	2800.00 g



FL H M POWER SUPPLY V

Materials & Colors

Body material		Aluminum	
Glow Wire Test according to IEC 60695-2-12		650 °C	
Mercury content		0.0 mg	

Application & Mounting

Ambient temperature range	-40+50 °C
Temperature range at storage	-40+70 °C

Type of protection	IP66/IP66	
Protection class IK (shock resistance)	IK08	
Dimmable	Yes	
Type of dimming	DALI	
Mounting location	Wall / Pole / Floor	
With light source	No	
Replaceable light source	No	

Lifespan

Certificates & Standards

Standards	CE / LVD / EMC / ROHS / REACH / SLR / ENEC
Luminaire with limited surface temperature, "D sign"	No

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	Floodlight High Mast
PDF	User instruction / safety instructions	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
PDF	Legal information	FL H M
PDF	Legal information	FL H M LUM V_POWER SUPPLY_PONTER HOLDER_ CUT OFF HOOD_ WIRE GUARD
PDF	Declarations of conformity	CE Declaration FL H M
PDF	Declarations of conformity UKCA	FL HIGH MAST
PDF	Certificates	FL H M
PDF	Certificates	FL H M LUM V
PDF	EU Data Act	DALI LED Driver and Luminaires
	Tender texts D	Document name
	Tender documents F	ELOODLIGHT HIGH MAST POWER SUPPLY 300W DALI-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854196607	Folding box	230 mm x 70 mm x 328 mm	2943.00 g	5.28 dm ³
4099854196614	Shipping box	348 mm x 306 mm x 260 mm	12273.00 g	27.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.