

PRODUCT DATASHEET

PL FLEX 600 DALI S 30W 840 U19

PANEL FLEX 600 UGR<19 DALI | Square recessed panel luminaire with low glare, for 600 x 600 mm ceiling systems and DALI-2 technology



Areas of application

- Suitable for recessed ceiling systems with grid size of 600 x 600 mm
- Direct replacement for recessed luminaires with fluorescent lamps
- Offices, conference rooms
- Reception areas, foyers, corridors, elevators

Product benefits

- Suitable luminaire for VIVARES and other DALI-2 Light Management Systems
- High lumen output with up to 4860 lm
- Energy savings thanks to high system efficacy: up to 160 lm/W
- Good glare reduction ($UGR \leq 19$)
- High color consistency with SDCM 3
- External driver for extended flexibility and easy installation
- Low flicker light thanks to special electronic control gear
- Tool-free electrical connection due to push button connector
- Through-wiring possible with included connector box
- Decentral emergency lighting possible with separately available LEDVANCE Emergency Conversion Box
- Extended services such as energy monitoring and remote maintenance possible with DALI versions
- 7 years guarantee

Product features



- IoT-ready luminaire with DALI-2 technology
- Suitable for central battery emergency installations acc. to EN 60598-2-22
- Lifetime (L80/B10): 100,000 h (at 25 °C), (L90/B10): 50,000 h (at 25 °C)
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Extruded aluminum frame, metal housing
- Polystyrene diffuser


TECHNICAL DATA

Electrical data


Nominal wattage	30.00 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	140.000 mA
Inrush current	4.4 A
Inrush current time T_{h50}	440 μ s
Max. number of luminaires per miniature circuit breaker B16	40
Max. number of luminaires per miniature circuit breaker C10	41
Max. number of luminaires per miniature circuit breaker C16	66
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	II
Operating mode	External LED driver
Dimming interface	DALI-2 / IoT

Photometrical data


Luminous flux	4860 lm
Luminous efficacy	160 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	≤ 3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	90 °
UGR	< 19



PL FLEX 600 DALI S 30W 4000K
U19 4860lm




PL FLEX 600 DALI S 6W 4000K
U19 750lm EM



PL FLEX 600 DALI S 30W 4000K
U19 4860lm

Dimensions & Weight

Length	595.00 mm
Width	595.00 mm
Height	32.00 mm
Product weight	1600.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C

Mercury content	0.0 mg
-----------------	--------

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal, 5-Pole (L, N, PE, DA+, DA-)
Type of protection	IP40/IP20
Protection class IK (shock resistance)	IK02
Dimmable	Yes
Type of dimming	DALI2
IoT ready	Support of DALI data type PART 251, 252, 253 ¹⁾
Mounting type	Recessed/Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Mounting length	595.00 mm
Mounting width	595.00 mm
Mounting depth	50 mm
Adjustable	No
With light source	Yes
Replaceable light source	No

¹⁾ Internet of Things. Supports data transfer via gateway to cloud-based monitoring platforms, such as LEDVANCE VIVARES Cloud

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	100000 h ¹⁾
Lifespan L80/B50 at 25 °C	100000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	700 mA
ECG - Output ripple current	< 5 %
ECG - Length	110 mm
ECG - Width	75 mm

ECG - Height	25 mm
Recommended control gear	OTi DALI 50/220...240/1A4 NFC

Emergency lighting

Type of Emergency Lighting (EL)	Optional EL unit (battery and controller) for decentral operation available separately / EL certified driver (0Hz / DC operation) for central battery operation included
Wattage in emergency operation mode	6 W
Luminous flux in emergency operation mode	700 lm

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD / EL
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	By the end consumer

Additional product data

Added function	VIVARES
----------------	---------

Accessories Optional

Product image	Product name	EAN
	DR DS-P- 30/220-240/700 PL FLEX 600	4058075843684
	EM CONVERSION BOX	4058075237025
	PANEL Suspension Kit	4058075402928
	PANEL RECESSED MOUNT CLIPS VAL 4x	4058075409859

Product image	Product name	EAN
	PANEL 600 SURFACE MOUNT KIT H75	4058075472914

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Connector box with 5-pole terminal included
- Security rope for luminaire included
- Security brackets preinstalled
- External control gear included
- Suitable for use with separate Emergency Conversion Box
- Serviceable luminaire: Upgrades and replacements available

Upgrade and replacement components

Components Light Control		
Product image	Product name	EAN
	MANUAL CONTROL UNIT SELECT DALI-2	4058075837485
	MANUAL CONTROL UNIT SELECT DALI-2 TW	4058075837508
	MANUAL CONTROL UNIT SELECT DALI-2 EXCHANGEABLE COVER TW	4058075837522
	MANUAL CONTROL UNIT TOUCH DALI-2 TW	4058075837560
	MANUAL CONTROL UNIT TOUCH DALI-2	4058075837546

Product image	Product name	EAN
	PUSH CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075837584
	SURFACE MOUNT FRAME	4058075843561
	PUSHBUTTON COUPLER DALI-2	4058075837607
	FLEX CONTROL UNIT IOT DALI-2 HCL TW	4058075841888
	FLEX CONTROL UNIT FLUSH MOUNT DALI-2 TW	4058075841901
	FLEX CONTROL UNIT DALI-2 TW	4058075843844
	FLEX CONTROL UNIT REAL-TIME-CLOCK DALI-2 HCL TW	4058075841925
	SENSOR DALI-2 LIGHT/PRESENCE-6 INFRARED CEILING INTEGRATION	4058075837621
	SENSOR DALI-2 LIGHT/PRESENCE-8 INFRARED CEILING INTEGRATION	4058075841949
	SENSOR DALI-2 LIGHT/PRESENCE-40X5 INFRARED CEILING INTEGRATION	4058075843868
	SENSOR DALI-2 LIGHT/PRESENCE-24 INFRARED CEILING MOUNTING	4058075843882

Product image	Product name	EAN
	SENSOR CEILING MOUNTING KIT	4058075843905

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	PANEL FLEX
 Legal information	LSI PANEL FLEX
 Legal information	Legal Insert PL FLEX
 Legal information	Informationstext 18 Abs 4 ElektroG
 Legal information	EM Insert PL FLEX
 Declarations of conformity	PL FLEX
 Declarations of conformity UKCA	PL FLEX
 EU Data Act	DALI LED Driver and Luminaires

Photometric and lighting design files	Document name
 IES file (IES)	PL FLEX 600 DALI S 30W 4000K U19 4860lm
 IES files (IES, additional)	PL FLEX 600 DALI S 3W 4000K U19 400lm EM BOX
 IES files (IES, additional)	PL FLEX 600 DALI S 6W 4000K U19 750lm EM
 LDT file (Eulumdat)	PL FLEX 600 DALI S 30W 4000K U19 4860lm
 LDT files (Eulumdat, additional)	PL FLEX 600 DALI S 3W 4000K U19 400lm EM BOX
 LDT files (Eulumdat, additional)	PL FLEX 600 DALI S 6W 4000K U19 750lm EM


Photometric and lighting design files		Document name
	ULD file (DIALux)	PL FLEX 600 DALI S 30W 840 U19
	ROLF file (RELUX)	PL FLEX 600 DALI S 30W 840 U19
	UGR file (UGR table)	PL FLEX 600 DALI S 30W 4000K U19 4860lm
	UGR file (UGR table)	PL FLEX 600 DALI S 3W 4000K U19 400lm EM BOX
	UGR file (UGR table)	PL FLEX 600 DALI S 6W 4000K U19 750lm EM
	Light distribution curve type cone	PL FLEX 600 DALI S 30W 4000K U19 4860lm
	Light distribution curve type cone	PL FLEX 600 DALI S 6W 4000K U19 750lm EM
	Light distribution curve type polar	PL FLEX 600 DALI S 30W 4000K U19 4860lm
CAD/BIM files		Document name
	BIM Revit 3D	PL FLEX
	CAD STEP 3D	PL FLEX 600
Tender texts		Document name
	Tender documents	PANEL FLEX 600 UGR19 DALI 30W 840 U19-EN



LOGISTICAL DATA


Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854276620	Folding box 1	35 mm x 685 mm x 600 mm	2055.00 g	14.39 dm ³
4099854276637	Shipping box 4	705 mm x 160 mm x 625 mm	9301.00 g	70.50 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



																																					
DLI DS-P-30/220-840/750 30W • 20W • 21W • 17W DLI DS-P-30/220-840/750 32W • 27W • 22W • 17W																																					
PANEL FLEX 600 / 600*	DRIVER																																				
PL FLEX 600 S 30W 840 PS (40W W / 40W W 200W DC) PL FLEX 600 S 30W 840 U19 PS (40W W / 40W W 200W DC)	DLI DS-P-30/220-840/750 PL FLEX 600 LAN 60807540384 <table> <tr><th>W LED W</th><th>lm EM 80</th><th>lm DC</th><th>lm W</th></tr> <tr><td>30</td><td>700</td><td>4800</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4100</td><td>180</td></tr> <tr><td>31</td><td>600</td><td>5510</td><td>187</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> <tr><td>30</td><td>700</td><td>4800</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4100</td><td>180</td></tr> <tr><td>31</td><td>600</td><td>5400</td><td>184</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> </table>	W LED W	lm EM 80	lm DC	lm W	30	700	4800	180	30	600	4100	180	31	600	5510	187	17	410	2800	108	30	700	4800	180	30	600	4100	180	31	600	5400	184	17	410	2800	108
W LED W	lm EM 80	lm DC	lm W																																		
30	700	4800	180																																		
30	600	4100	180																																		
31	600	5510	187																																		
17	410	2800	108																																		
30	700	4800	180																																		
30	600	4100	180																																		
31	600	5400	184																																		
17	410	2800	108																																		
PL FLEX 600 S 30W 840 PS (40W W / 40W W 200W DC) PL FLEX 600 S 30W 840 U19 PS (40W W / 40W W 200W DC)	DLI DS-P-30/220-840/750 PL FLEX 600 LAN 60807540384 <table> <tr><th>W LED W</th><th>lm EM 80</th><th>lm DC</th><th>lm W</th></tr> <tr><td>30</td><td>700</td><td>5000</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4400</td><td>180</td></tr> <tr><td>32</td><td>510</td><td>2800</td><td>107</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> <tr><td>30</td><td>700</td><td>5100</td><td>181</td></tr> <tr><td>31</td><td>600</td><td>4500</td><td>180</td></tr> <tr><td>32</td><td>510</td><td>2810</td><td>108</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> </table>	W LED W	lm EM 80	lm DC	lm W	30	700	5000	180	30	600	4400	180	32	510	2800	107	17	410	2800	108	30	700	5100	181	31	600	4500	180	32	510	2810	108	17	410	2800	108
W LED W	lm EM 80	lm DC	lm W																																		
30	700	5000	180																																		
30	600	4400	180																																		
32	510	2800	107																																		
17	410	2800	108																																		
30	700	5100	181																																		
31	600	4500	180																																		
32	510	2810	108																																		
17	410	2800	108																																		
PL FLEX 600 DALI S 30W 840 PL FLEX 600 DALI S 30W 840 U19 PL FLEX 600 DALI S 30W 840 U19 (40W W / 40W W 200W DC)	DLI DS-P-30/220-840/750 PL FLEX 600 LAN 60807540384 <table> <tr><th>W LED W</th><th>lm EM 80</th><th>lm DC</th><th>lm W</th></tr> <tr><td>30</td><td>700</td><td>4800</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4100</td><td>180</td></tr> <tr><td>31</td><td>600</td><td>5400</td><td>184</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> <tr><td>30</td><td>700</td><td>4800</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4100</td><td>180</td></tr> <tr><td>31</td><td>600</td><td>5400</td><td>184</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> </table>	W LED W	lm EM 80	lm DC	lm W	30	700	4800	180	30	600	4100	180	31	600	5400	184	17	410	2800	108	30	700	4800	180	30	600	4100	180	31	600	5400	184	17	410	2800	108
W LED W	lm EM 80	lm DC	lm W																																		
30	700	4800	180																																		
30	600	4100	180																																		
31	600	5400	184																																		
17	410	2800	108																																		
30	700	4800	180																																		
30	600	4100	180																																		
31	600	5400	184																																		
17	410	2800	108																																		
PL FLEX 600 DALI S 30W 840 U19	DLI DS-P-30/220-840/750 PL FLEX 600 LAN 60807540384 <table> <tr><th>W LED W</th><th>lm EM 80</th><th>lm DC</th><th>lm W</th></tr> <tr><td>30</td><td>700</td><td>4800</td><td>180</td></tr> <tr><td>30</td><td>600</td><td>4100</td><td>180</td></tr> <tr><td>31</td><td>600</td><td>5400</td><td>184</td></tr> <tr><td>17</td><td>410</td><td>2800</td><td>108</td></tr> </table>	W LED W	lm EM 80	lm DC	lm W	30	700	4800	180	30	600	4100	180	31	600	5400	184	17	410	2800	108																
W LED W	lm EM 80	lm DC	lm W																																		
30	700	4800	180																																		
30	600	4100	180																																		
31	600	5400	184																																		
17	410	2800	108																																		



References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.