

PRODUCT DATASHEET LED T5 FC 40/55 EXTERNAL 21.5W 865 2GX13

LED T5 FC EXTERNAL | LED T5 FC EXTERNAL for LED DRIVER DALI



Areas of application

- Shops, hotels and restaurants
- Public buildings



Product benefits

- Compatible with LED driver DR DALI-P -30/220-240/700 and DR DALI-P -42/220-240/1A0 (4058075845367, 4058075845381)
- Simple upgrade to dimmable LED system
- Hassle free application, no ballast compatibility check necessary
- 5 years guarantee

Product features

- Designed to power with LED DRIVER DALI PERFORMANCE
- Single-ended round LED lamp
- Suitable illumination within ambient temperatures from -20...+45 °C
- Lifetime (L70/B50) up to 50,000 h (at 25 °C)
- LED replacement for traditional T5 fluorescent circular lamps





TECHNICAL DATA

Electrical data

Nominal wattage	21.5 W
Nominal voltage	33 V
Operating mode	EXT
Nominal current	650 mA
Type of current	DC
Inrush current	3.3 A ¹⁾
Operating frequency	0 Hz
Mains frequency	0 Hz
Total harmonic distortion	< 20 %
Power factor λ	0.90

^{1) @}Th50 220us

Photometrical data

Luminous flux	3200 lm
Luminous efficacy	148 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool Daylight
Color temperature	6500 K
Color rendering index Ra	80
Light color	865
Standard deviation of color matching	≤5 sdcm
Rated LLMF at 6,000 h	0.90
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0,4



EPREL data spectral diagram PROF LEDr 6500K

Light technical data

Beam angle	120 °
Warm-up time (60 %)	< 2.00 s
Starting time	< 1.0 s

Dimensions & Weight



Overall length	300.00 mm
Length with base excl. base pins/connection	300,00 mm
Diameter	16.50 mm
Product weight	121.00 g

Temperatures & operating conditions

Ambient temperature range	-20+45 °C ¹⁾
Maximum temperature at tc test point	67 °C

¹⁾ Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	0.90

Additional product data

Base (standard designation)	2GX13
Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	Yes

Certificates & Standards

Energy efficiency class	D 1)
Energy consumption	22.00 kWh/1000h
Type of protection	IP20
Standards	CE / UKCA
Photobiological safety group acc. to EN62778	RG0

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Country-specific categorizations			
Order reference	LEDT5 FC40/55 E		
LOGISTICAL DATA			
Temperature range at storage	-20+80 °C		
Energy labelling regulation data acc EU 2019/2015			
Lighting technology used	LED		
Non-directional or directional	NDLS		
Mains or non-mains	NMLS		
Light source cap-type (or other electric interface)	2GX13		

No

No

No

No

No

16.50 mm

Connected light source (CLS)

Color-tuneable light source

Envelope

Height

Correlated colour temperature type SINGLE_VALUE 0 W Standby power

Claim of equivalent power No

Length 300.00 mm

Width 16.50 mm

Chromaticity coordinate x 0,312

Chromaticity coordinate y 0,328

R9 Colour rendering index 1

Beam angle correspondence SPHERE_360 Survival factor 0,90

Displacement factor 0,90

LED light source replaces a fluorescent light source No

EPREL ID	1956105
Model number	AC63044

Accessories Mandatory

Product image	Product name	EAN
	DR DALI-P -30/220-240/700	4058075845367
	DR DALI-P -42/220-240/1A0	4058075845381

Safety advice

- Suitable for indoor applications.
- The operating temperature range of LED tube is restricted. In case of doubt regarding suitability of the application please measure Tc temperature on the product prior to installation.
- Not suitable for operation with 230 V line voltage or electronic control gear.
- Disconnect mains before installation.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	LEDT5 FC22 FC40/55 EXT P	
POF	Extended installation guide	LEDVANCE Luminaire conversion checklist	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
POF	Declarations of conformity	LED T5 FC EXT	
POF	Declarations of conformity UKCA	LED T5 FC EXT	
	Photometric and lighting design files	Document name	
	IES file (IES)	LED T5 EXT FC40 55 P 21.5W 865 2GX13 LEDV	

Photometric and lighting design files	Document name
LDT file (Eulumdat)	LED T5 EXT FC40 55 P 21.5W 865 2GX13 LEDV
UGR file (UGR table)	LED T5 EXT FC40 55 P 21.5W 865 2GX13 LEDV
Light distribution curve type cone	LED T5 EXT FC40 55 P 21.5W 865 2GX13 LEDV
Light distribution curve type polar	LED T5 EXT FC40 55 P 21.5W 865 2GX13 LEDV
Spectral power distribution	EPREL data spectral diagram PROF LEDr 6500K

Tender texts	Document name
Tender documents	LED T5 FC EXTERNAL P 21.5W 865 2GX13-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854300905	Folding box 1	26 mm x 307 mm x 308 mm	229.00 g	2.46 dm ³
4099854300912	Shipping box 10	325 mm x 274 mm x 333 mm	2904.00 g	29.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/ledtube

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.