

PRODUCT DATASHEET

FLASHLIGHT SPOTLIGHT TRANSFORM

FLASHLIGHT SPOTLIGHT TRANSFORM | Outdoor mobiles



Areas of application

- Multifunctional

Product benefits

- 4 operating modes: 1 press: bright light 300 lm, 2nd press: soft light 100 lm, 3rd press: side light, 4th press: flashing mode
- 1,5 h of running at full brightness
- 3,5 h of running at side light mode
- 6 hours to fully charge from empty-to-full
- Battery capacity: 2400 mA
- Power Bank mode

Product features

- Charging indicator
- Convenient button for switching modes
- COB LED for side light.
- Type of protection: IP64

TECHNICAL DATA

Electrical data

Nominal wattage	3.00 W
Inrush current	1 A
Inrush current time T _{h50}	0.5 s
Operating mode	Battery

Photometrical data

Luminous flux	300 lm
Luminous efficacy	100 lm/W
Color temperature	6500 K
Light color (designation)	Cool White
Color rendering index Ra	70

Dimensions & Weight

Length	110.00 mm
Width	110.00 mm
Height	160.00 mm
Product weight	560.00 g

Materials & Colors

Product color	Black
Housing color	Black
Body material	ABS I TPR (Thermoplastic rubber)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	USB Type-C
Dimmable	No
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

BATTERY

Battery size [GMS]	18650
Battery charging time	6 h




Certificates & Standards

Standards	CE / UKCA
Replaceable light source (EPREL)	Not replaceable

EQUIPMENT / ACCESSORIES

– USB C cable

DOWNLOAD DATA

Documents and certificates		Document name
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	FLASHL
	Declarations of conformity	CE Declaration Flashlight

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854175763	Folding box 1	212 mm x 117 mm x 167 mm	637.00 g	4.14 dm ³
4099854175770	Shipping box 20	600 mm x 355 mm x 455 mm	13881.00 g	96.92 dm ³
4099854440113	Shipping box 10	393 mm x 285 mm x 393 mm	5920.00 g	44.02 dm ³
4099854583964	Shipping box 10	610 mm x 350 mm x 250 mm	7423.00 g	53.38 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.