

# PRODUCT DATASHEET Decor Drums Pendant 3XGU10 2XLED Black

Decor Drums | Decorative luminaires made of aluminium with GU10 socket



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

## Product benefits

- High-quality look and feel
- High-quality housing with a matt black surface
- Minimalistic style fits to every room
- Different types of luminaires with the same design language maintain a consistent style at home
- Inline-switch for table and floor luminaire
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

### Product features

- Housing material: aluminum
- Textile cable



# TECHNICAL DATA

# Electrical data


Nominal wattage	7.50 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	60.000 mA
Inrush current	0.06 A
Inrush current time T <sub>h50</sub>	70 μs
Max. number of luminaires per miniature circuit breaker B16	110
Max. number of luminaires per miniature circuit breaker C10	88
Max. number of luminaires per miniature circuit breaker C16	141
Power factor $\lambda$	> 0.5
Total harmonic distortion	64 %
Protection class	II .
Operating mode	Mains voltage

# Photometrical data

Luminous flux	460 lm
Total luminous flux of contained light sources	680 lm
Luminous efficacy	61 lm/W
Color temperature	3000 K
Reference control setting of contained light source (Kelvin)	3000 K
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	< 0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	26 °

# Dimensions & Weight

Length	825.00 mm
Width	56.00 mm
Height	1240.00 mm
Product weight	1685.00 g



DECOR DRUMS PENDANT 3XGU10 2XLED BK

### Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Suspended
With light source	Yes
Replaceable light source	No
Holder designation	GU10

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No

# Additional product data

Product remark	Maximum bulb wattage: 5 W LED
Number of illuminants	2

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	
PDF	Legal information	DECOR DRUMS/CIRCLE
PDF	Declarations of conformity	DECOR LUM
PDF	Declarations of conformity UKCA	DECOR LUM

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075838581	Folding box	112 mm x 137 mm x 873 mm	1980.00 g	13.40 dm <sup>3</sup>
4058075838598	Shipping box 4	890 mm x 245 mm x 300 mm	8881.00 g	65.42 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.