

PRODUCT DATASHEET

Decor Circle Floor 17W CLICKCCT Black

Decor Circle | Decorative luminaires made of acrylic and metal with LED



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- High-quality look and feel
- Minimalistic design with elegant decorative lighting
- Different types of luminaires with the same design language maintain a consistent style at home
- Easy mounting
- Highly versatile due to selectable CCT

Product features

- Housing material: acrylic
- High-power LED



TECHNICAL DATA**Electrical data**


Nominal wattage	17.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	90.000 mA
Inrush current time T _{h50}	192 µs
Power factor λ	0.85
Protection class	II
Operating mode	Mains voltage

Photometrical data

Luminous flux	930 lm
Total luminous flux of contained light sources	1600 lm
Luminous efficacy	55 lm/W
Color temperature	3000 K / 4000 K / 6500 K
Reference control setting of contained light source (Kelvin)	3000 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcn
Flickering metric (Pst LM)	0.6
Stroboscope effect metric (SVM)	0,15
Photobiological safety group acc. to EN62778	RG0
Beam angle	300 °

Dimensions & Weight

Length	340.00 mm
Width	230.00 mm
Height	1525.00 mm
Product weight	3540.00 g
Cable length	1800 mm



DECOR CIRCLE FLOOR 17W
CLICKCCT

Materials & Colors

Product color	Black
Housing color	Black
Body material	Polymethylmethacrylate (PMMA)
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	No
Mounting type	Standing
Mounting location	Floor
Adjustable	No
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE
-----------	----

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------


Additional product data

Product remark	Available from July 2025
Number of illuminants	1

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR CIRCLE TABLE+FLOOR CLICKCCT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075847361	Folding box 1	126 mm x 272 mm x 563 mm	3875.00 g	19.30 dm ³
4058075847378	Shipping box 3	576 mm x 287 mm x 400 mm	12551.00 g	66.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.