

PRODUCT DATASHEET

Decor Felt Hat Pendant 1XE27 Dark Gray

Decor Felt Hat | Decorative luminaires made of felt with E27 socket



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

Product benefits

- Eye-catching luminaire made of felt
- Design delights your home with a warm atmosphere
- Lampshade made of recycled materials
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

Product features

- Housing material: felt
- Textile cable




TECHNICAL DATA

Electrical data

| | |
|------------------|---------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Protection class | I |
| Operating mode | Mains voltage |

Dimensions & Weight

| | |
|----------------|------------|
| Diameter | 500.00 mm |
| Height | 1500.00 mm |
| Product weight | 500.00 g |



DECOR FELT HAT PENDANT
1XE27 DG

Materials & Colors

| | |
|--|------------|
| Product color | Dark gray |
| Housing color | Dark gray |
| Body material | Felt Steel |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|-----------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | No |

| | |
|--------------------------|-----------|
| Mounting type | Suspended |
| With light source | No |
| Replaceable light source | No |
| Holder designation | E27 |

Certificates & Standards

| | |
|--|-----------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |




Additional product data

| | |
|-----------------------|-------------------------------|
| Product remark | Maximum bulb wattage: 6 W LED |
| Number of illuminants | 1 |

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|---------------------------------|
|  | User instruction / safety instructions | DECOR FELT HAT PENDANT 1XE27 DG |
|  | Declarations of conformity | DECOR LUM |
|  | Declarations of conformity UKCA | DECOR LUM |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075841581 | Folding box 1 | 182 mm x 482 mm x 507 mm | 1011.00 g | 44.48 dm ³ |
| 4058075841598 | Shipping box 2 | 498 mm x 378 mm x 532 mm | 3286.00 g | 100.15 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.