

PRODUCT DATASHEET SMART+ ZIGBEE Plug EU White

SMART+ ZIGBEE Plug | Plug with smart socket and energy meter to control non smart devices with ZigBee technology



Areas of application

 Wherever non-smart devices need to be integrated into compatible smart home systems

Product benefits

- Small design, compatible with all types of sockets and does not interfere with neighboring sockets
- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Monitors energy usage of connected devices and tracks the energy consumption

Product features


- Control via compatible smart home system, or on/off button on the device
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Network protocol: ZigBee 3.0
- Scheduling
- High switching power: up to 2,300 W / 10 A
- Energy meter
- For full functionality, connection to a compatible smart home System (gateway and app) required

TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Nominal current	10 A
Mains frequency	50 Hz

Dimensions & Weight



Product weight	76.6 g
Diameter	48 mm
Height	82.4 mm

Lifespan

Number of switching cycles	10000
rtarribor or ovintorining of oldo	10000

Colors & materials

Product color	White
1 Toddot Goldi	White

Temperatures & operating conditions

Capabilities

Type of connection	Plug	
Compatible smart home technology	Amazon Alexa / Google Home / Philips Hue	

Certificates & Standards

Standards	CE
Protection class	T. Control of the con
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Control via app requires a compatible Smart home system

Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (for max. 10 A)
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates Document name	
PDF	User instruction / safety instructions ZB_PLUG_EU	
PDF	Legal information	Safety insert G11222558
PDF	Declarations of conformity	SMART ZB PLUG
PDF	EU Data Act	SMART ZigBee Plugs

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854419263	Folding box	56 mm x 76 mm x 90 mm	108.60 g	0.38 dm ³
4099854419270	Shipping box 4	162 mm x 122 mm x 106 mm	507.04 g	2.09 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.