

- Cable length of the DALI control cable: up to 300 m
- Length of the pushbutton cable: up to 50 m

TECHNICAL DATA

Electrical data

Nominal wattage	3.00 W
Nominal voltage	220...240 V
Type of current	DC
Input current	22 mA
Mains frequency	50...60 Hz
Operating frequency	50/60 Hz

Dimensions & Weight



Length	49.00 mm
Width	48.00 mm
Height	22.00 mm
Wire preparation length, input side	5...6 mm
Product weight	40.00 g

Colors & materials

Product color	Light grey
---------------	------------

Temperatures & operating conditions

Ambient temperature range	-20...+60 °C
Maximum temperature at tc test point	70 °C
Temperature range in operation	-20...+60 °C

Lifespan

Number of switching cycles	30000
----------------------------	-------

Additional product data

Number of control outputs	1
Max. connectable push button couplers / sensors	4
Max. number of connected drivers	32
Commissioning App	App (Android/ iOS)
Light control tool App	App (Android/ iOS)
Groups	4

Capabilities

Dimmable	No
Dimming interface	DALI-2
Number of control outputs	1
Type of installation	Integrated in flush device box









Certificates & Standards


Approval marks – approval	CE
Protection class	II
Type of protection	IP20


EQUIPMENT / ACCESSORIES

– App for iOS and Android available for free in the app store

DOWNLOAD DATA

Documents and certificates	Document name
 User instruction / safety instructions	FLEX CU FLUSH MOUNT DALI 2 TW
 User instruction / safety instructions	FLEX CU FLUSH MOUNT DALI-2 TW
 Extended installation guide	Application Guide FLEX Control Units DALI2
 Extended installation guide	Application Guide FLEX Control Units DALI-2
 On-Pack-Info	Privacy Information LEDVANCE DALI CONFIG APP EN
 On-Pack-Info	Privacy Information LEDVANCE DALI CONTROL APP EN
 Legal information	Informationstext 18 Abs 4 ElektroG
 Declarations of conformity	FLEX CU FLUSH MOUNT DALI-2 TW

CAD/BIM files	Document name
 CAD STEP 3D	FLEX CU FLUSH MOUNT DALI-2 TW


Tender texts	Document name
 Tender documents	DALI-2 CONTROL UNITS FLUSH MOUNT DALI-2 TW-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075841901	Folding box 1	81 mm x 81 mm x 46 mm	57.00 g	0.30 dm³
4058075841918	Shipping box 60	344 mm x 254 mm x 278 mm	3847.00 g	24.29 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION



References / Links

– For current information see www.ledvance.com/light-management-systems

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.