



PRODUCT DATASHEET

FL 100 P 69W 10KLM 865 PS SY100 WT

FLOODLIGHT 100 | Versatile floodlight with up to 10000 lm light output



PERFOR-
MANCE
CLASS

Areas of application

- Replacement for floodlights with halogen lamps
- Outdoor use (IP66)
- D-sign according to EN 60598-2-24 for fire-risk commercial unit, e.g. by accumulation of dust
- Public areas
- Building facades
- Construction areas
- Parking

Product benefits

- Breather membrane to optimize air exchange, without compromising IP protection
- Highly versatile due to selectable power steps (Multi Lumen) on the housing
- Robust cable gland with integrated waterstop function
- Safe and very uniform illumination, due to frosted and tempered glass diffuser
- Bright, robust and durable
- Energy savings of up to 90 % compared to halogen lamp floodlights
- No upper light output ratio (ULOR 0%) when mounted at 0° tilt

Product features

- High luminous efficacy: up to 150 lm/W
- Type of protection: IP66
- Pre-installed, flexible 1 m cable (H05RN-F), wrapped 3 x 1.0 mm² single wires
- Reflector-based, symmetric light distribution with 100° x 100° beam angle
- Mounting bracket with 30° angle and wide rotation area


502 Bad Gateway

TECHNICAL DATA**Electrical data**


Nominal wattage	69 W / 53 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	310/260 mA
Inrush current	18.8 A
Inrush current time T_{h50}	86.2 μ s
Max. number of luminaires per miniature circuit breaker B16	40
Max. number of luminaires per miniature circuit breaker C10	25
Max. number of luminaires per miniature circuit breaker C16	25
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Surge capability (L-N)	4 kV
Surge capability (L/N-Ground)	6 kV
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	10000 lm / 8000 lm
Luminous efficacy	145 lm/W
Color temperature	6500 K
Light color (designation)	Cool Daylight
Color rendering index Ra	80
Standard deviation of color matching	5 sdc _m
Stroboscope effect metric (SVM)	≤0.9
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	100 ° x 100 °



FL 100 P 69W 10KLM 865 PS SY100 WT



FL 100 P 69W 10KLM 865 PS SY100 WT

Dimensions & Weight

Length	236.00 mm
Width	52.00 mm
Height	236.00 mm
Product weight	1712.00 g
Cable length	1000 mm



Materials & Colors

Product color	White
Housing color	White

RAL Color (most similar)	RAL 9003
Body material	Aluminum
Cover material	Glass
Light emitting surface material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-30...+50 °C
Temperature range at storage	-40...+70 °C
Type of connection	Cable, 3-pole
Type of protection	IP66
Protection class IK (shock resistance)	IK08
Corrosion resistance class acc. to EN 12944	C4
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Pole / Floor / Ceiling
Application environment	Outdoor
Adjustable	Yes
With light source	Yes
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	75000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	550 mA
ECG - Output ripple current	< 20 %

Certificates & Standards

Standards	CE / CB / ENEC / EAC / UKCA / EPD
Luminaire with limited surface temperature, "D sign"	Yes
Ball shot safe	No
EPD	LEDV-00030-V01.01-EN
Replaceable light source (EPREL)	Not replaceable

502 Bad Gateway

Additional product data

Added function	MULTI SELECT
----------------	--------------

Accessories Optional

Product image	Product name	EAN
	FL TRAVERSE 1/2 42/60/76MM	4099854680038

Safety advice

– Max. wind load surface 0.045 m²

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	G11193710_UI_Floodlight_65W-200W
	Legal information	Insert_LSI_Floodlight_69W-167W_G11195968
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety Insert G11205496
	Legal information	Legal Insert G11257402
	Declarations of conformity	FLOODLIGHT GEN4
	EPD	EPD EN FLOODLIGHT GEN 4 MP PHOTOCELL

Photometric and lighting design files		Document name
	IES file (IES)	FL 100 P 69W 10KLM 865 PS SY100 WT
	LDT file (Eulumdat)	FL 100 P 69W 10KLM 865 PS SY100 WT
	ULD file (DIALux)	FL 100 P 69W 10KLM 865 PS SY100 WT
	ROLF file (RELUX)	FL 100 P 69W 10KLM 865 PS SY100 WT

Photometric and lighting design files		Document name
	UGR file (UGR table)	FL 100 P 69W 10KLM 865 PS SY100 WT
	Light distribution curve type cone	FL 100 P 69W 10KLM 865 PS SY100 WT
	Light distribution curve type polar	FL 100 P 69W 10KLM 865 PS SY100 WT
CAD/BIM files		Document name
	BIM Revit 3D	Floodlight G4
	CAD STEP 3D	FL G4 69W
Tender texts		Document name
	Tender documents	FLOODLIGHT 100 69W 10KLM 865 PS SY100 WT-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854306228	Folding box 1	78 mm x 255 mm x 237 mm	1868.00 g	4.71 dm³
4099854306235	Shipping box 4	332 mm x 271 mm x 264 mm	7976.00 g	23.75 dm³



The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION

Technical drawing of the floodlight showing dimensions A, B, C, and D. The drawing is a side view of the floodlight, which has a rectangular body with a mounting bracket on the left side. Dimension A is the total width of the floodlight. Dimension B is the width of the mounting bracket. Dimension C is the distance from the mounting bracket to the center of the floodlight. Dimension D is the distance from the mounting bracket to the right edge of the floodlight.

	A	B	C		
69W	150	108	8.5	2x M8	0.045 m²
100W	150	108	10.5	2x M8	0.070 m²
135W	170	118	10.5	2x M8	0.088 m²
167W	170	118	12.5	2x M10	0.105 m²

					230 Vac			
	A	B	C		C10A	B15A	C16A	
69W	150	108	8.5	2x M8	0.045 m²	25	40	41
100W	150	108	10.5	2x M8	0.070 m²	6	9	9
135W	170	118	10.5	2x M8	0.088 m²	4	4	7
167W	170	118	12.5	2x M10	0.105 m²	4	4	7





FL 100P69W10KLM830PS SY100	53W/7320lm	69W/9150lm
FL 100P69W10KLM840PS SY100	53W/8000lm	69W/10000lm
FL 100P69W10KLM865PS SY100	53W/8000lm	69W/10000lm
FL 150P100W15KLM830PS SY100	83W/11670lm	100W/14000lm
FL 150P100W15KLM840PS SY100	83W/12500lm	100W/15000lm
FL 150P100W15KLM865PS SY100	83W/12500lm	100W/15000lm
FL 200P133W20KLM830PS SY100	117W/16275lm	133W/18600lm
FL 200P133W20KLM840PS SY100	117W/17500lm	133W/20000lm
FL 200P133W20KLM865PS SY100	117W/17500lm	133W/20000lm
FL 250P167W25KLM830PS SY100	150W/21060lm	167W/23400lm
FL 250P167W25KLM840PS SY100	150W/22500lm	167W/25000lm
FL 250P167W25KLM865PS SY100	150W/22500lm	167W/25000lm

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

502 Bad Gateway