

PRODUCT DATASHEET LS AY AC-CP P2 300 P

CONNECTOR FOR AC MAINS DIRECT | LED strip connector for AC mains supply



Areas of application

- General indoor illumination
- General outdoor illumination

Product benefits

- Easy installation of connector, no manual wiring required
- Simple and quick installation thanks to twist lock functionality

Product features

- Safe and professional connector of LED strips for 220-240V AC mains supply via prewired integrated over-current protection (3.15A)
- Type of protection: IP66

TECHNICAL DATA

Electrical data

Type of current	AC
-----------------	----

Dimensions & Weight



Length	440 mm
Width	23.0 mm
Height	23.0 mm
Cable cross-section, input side	1.0 mm ²
Product weight	78.00 g

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+45 °C
Temperature range in operation	-20+45 °C
Permitted rel. humidity during operation	093 %

Additional product data

Prod	uct remark	Available from September 2024
------	------------	-------------------------------

LOGISTICAL DATA

Temperature range at storage	-20+80 °C
	-

DOWNLOAD DATA

Documents and certificates		Document name	
User instruction / safety instructions		UI_LED STRIP_HV	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	

Documents and certificates		Document name	
PDF	Legal information	Safety Insert G11201420	
PDF	Declarations of conformity	LS LUM	
PDF	Declarations of conformity UKCA	LS LUM	

Tender texts	Document name
Tender documents	CONNECTOR FOR AC MAINS DIRECT P2 300 P-en


LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075844780	BAG 1	200 mm x 250 mm x 20 mm	94.00 g	1.00 dm ³
4058075844797	Shipping box 50	347 mm x 347 mm x 204 mm	5193.00 g	24.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

ADDITIONAL CATALOG INFORMATION





DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.