

# PRODUCT DATASHEET LS AY AC PLUG UK

POWER PLUGS FOR LED STRIP HIGH VOLTAGE 230V - UK | Power plug for LED strip 230V AC mains direct supply



# Areas of application

- General indoor illumination
- General outdoor illumination

## **Product benefits**

- Easy installation of connector, no manual wiring required

#### Product features

- Power cable with integrated twist lock functionality and cable length of 1,50 m
- Only suitable for UK region
- Type of protection: IP20

#### **TECHNICAL DATA**

## Electrical data

Type of current	AC

# Dimensions & Weight



Length	1570 mm
Width	23 mm
Height	23 mm
Product weight	195.00 g

## Colors & materials

Product color	White
Body material	Polycarbonate (PC)

# Temperatures & operating conditions

Ambient temperature range		-20+45 °C
Temperature range in operation		-20+45 °C
Permitted rel. humidity during oper	ation	093 %

# Additional product data

Product remark	Available from September 2024

# Certificates & Standards

e of protection IP2	P20
---------------------	-----

# LOGISTICAL DATA

Temperature range at storage	-20+80 °C
------------------------------	-----------

## DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	UI_LED STRIP_HV

Documents and certificates		Document name	
PDF	Legal information	Informationstext 18 Abs 4 ElektroG	
PDF Legal information		Safety Insert G11201420	
PDF	Declarations of conformity UKCA	LS LUM	

Tender texts	Document name
Tender documents	POWER PLUGS FOR LED STRIP HIGH VOLTAGE 230V UK PLUG-en


#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075844827	BAG 1	200 mm x 250 mm x 50 mm	211.00 g	2.50 dm <sup>3</sup>
4058075844834	Shipping box 50	357 mm x 357 mm x 264 mm	11232.00 g	33.65 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## ADDITIONAL CATALOG INFORMATION





## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.