

PRODUCT DATASHEET Floodlight EA 15W 840 Dark Grey

FLOODLIGHTS ENERGY EFFICIENCY | Floodlights with Energy Class A light source



Areas of application

- Outdoor
- Garages
- Building facades

Product benefits

- Very low energy consumption
- Quick and simple installation thanks to low profile, compact and light weight design

Product features

- Luminous efficacy of light source: up to 210 lm/W
- Very bright and functional outdoor LED luminaires
- Type of protection: IP65



TECHNICAL DATA

Electrical data


Nominal wattage	15.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	113.000 mA
Inrush current time T _{h50}	100 µs
Max. number of luminaires per miniature circuit breaker B16	58
Max. number of luminaires per miniature circuit breaker C10	46
Max. number of luminaires per miniature circuit breaker C16	74
Power factor λ	≥0.5
Total harmonic distortion	≤ 140 %
Protection class	1
Operating mode	Mains voltage

Photometrical data

Luminous flux	2600 lm
Total luminous flux of contained light sources	3150 lm
Luminous efficacy	173 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Photobiological safety group acc. to EN62778	RG1
Beam angle	95 °

Dimensions & Weight

Length	128.00 mm
Width	32.00 mm
Height	123.00 mm
Product weight	373.00 g
Cable length	1000 mm



FL EA 15W 840 BK

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Cable, 3-pole
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
Adjustable	Yes
With light source	Yes
Replaceable light source	No
· · · · · · · · · · · · · · · · · · ·	

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Number of illuminants empty

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	FL EA BK
PDF	Legal information	Safety insert G11220428
PDF	Declarations of conformity	FL EA_BK
PDF	Declarations of conformity UKCA	FL EA_BK

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854429514	Folding box	47 mm x 120 mm x 141 mm	407.00 g	0.80 dm ³
4099854429521	Shipping box	268 mm x 262 mm x 179 mm	3541.00 g	12.57 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.