

# PRODUCT DATASHEET LDVAL PAN 0606 33W DIM TRI UGR19

PANEL PLUS | Featuring dual wattage version, IP54, TRI CCT, phase dimming version and DALI version, complemented by a low-glare diffuser (UGR<19)



### Areas of application

- Offices, conference rooms
- Reception areas and foyers
- Entrances / Hallways
- Retail
- Hospitality
- Libraries, schools

## **Product benefits**

- Available in dual wattage version, phase dimming version and DALI version
- High luminous efficacy
- Good glare reduction (UGR < 19)

# **Product features**

- TRI colour in 3000K, 4000K and 5700K
- Beam angle: 90°
- Type of protection: IP54
- $-\,$  High luminous efficacy: up to 120 lm/W
- Pre-wired with flex and plug
- Lifetime up to 50,000 h

## **TECHNICAL DATA**

# Electrical data

Nominal wattage	33.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	200.000 mA
Power factor $\lambda$	> 0.90
Protection class	П
Operating mode	External LED driver

#### Photometrical data

Luminous flux	4000 lm	
Luminous efficacy	120 lm/W	
Color temperature	3000 5700 K	
Light color (designation)	Warm White / Cool White / Cool Daylight	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 5 sdcm	
Beam angle	90 °	
UGR	< 19	

# Dimensions & Weight

Length	595.00 mm
Width	595.00 mm
Height	32.00 mm
Product weight	1875.00 g

LED PERFORMANCE PANEL WV Backlit 0606 25W

## Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Mercury content	0.0 mg

# **Application & Mounting**

nbient temperature range	-10+40 °C
--------------------------	-----------

Type of protection	IP54/IP20
Dimmable	Yes
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting length	595.00 mm
Mounting width	595.00 mm
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C	50000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	50000 h <sup>1)</sup>

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

## Certificates & Standards

Replaceable light source (EPREL)  Not replaceable	Replaceable light source (EPREL)	
---	----------------------------------	--

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854247132	Folding box 1	641 mm x 38 mm x 603 mm	2171.00 g	14.69 dm³
4099854247149	Shipping box	662 mm x 254 mm x 630 mm	13671.00 g	105.93 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.