

# PRODUCT DATASHEET ULTRA COMMERCIAL DOWNLIGHT 14-19W 135MM TRI DIM

ULTRA COMMERCIAL DOWNLIGHT | The Ultra Commercial Downlight offers an economical solution for both new projects and the replacement of larger diameter luminaires, such as older compact fluorescent



#### Areas of application

- Public areas
- Reception areas and foyers
- Entrances / Hallways
- Retail and small shops
- Hospitality
- Commercial applications
- Lobbies

#### Product benefits

- Phase dim: 10.5W, 12W, 14W, 19/14W, 20/14W, 30/23W, 40/30W
- DALI: 11W, 14.5W, 18W, 18/15W, 20/16W, 29/23W, 39/29W
- Cut out size in 92mm, 118mm, 135mm, 160mm, 195mm, 240mm
- Available in phase dimming and DALI

### **Product features**

- TRI colour in 3000K, 4000K and 5700K
- Type of protection: IP54
- Pre-wired with 1.6m flex and plug
- Lifetime up to 50,000 h
- High luminous efficacy: up to 135 lm/W

## **TECHNICAL DATA**

## Electrical data

Nominal wattage	14.0 W / 19 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.90
Protection class	П
Operating mode	External LED driver

# Photometrical data

Luminous flux	1800 lm / 2100 lm / 2000 lm
Luminous efficacy	115 lm/W
Color temperature	3000 K / 4000 K / 5700 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	80
Beam angle	100 °
UGR	< 22

# Dimensions & Weight

Diameter	165.00 mm
Height	63.00 mm
Product weight	360.00 g

LDECO DL 135MM TRI

# Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Type of protection	IP54/IP20
Dimmable	Yes
Type of dimming	PHASE CUT

Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	135 mm
Replaceable light source	No

## Lifespan

Lifespan L70/B50 at 25 °C 50000 h 1)	

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

#### Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854333811	Folding box	233 mm x 176 mm x 90 mm	476.00 g	3.69 dm <sup>3</sup>
4099854333828	Shipping box 8	485 mm x 372 mm x 210 mm	4530.00 g	37.89 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.