

# PRODUCT DATASHEET

## OFFICE LINEAR SF V UPLIGHT MODULE

OFFICE LINEAR UPLIGHT MODULE | Uplight module for Office Linear surface rails



### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- General indoor illumination

### Product benefits

- High performance with CRI90
- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Highly versatile due to selectable CCT
- Easy installation
- 5 years guarantee

### Product features

- Modern design
- Lifetime (L70/B50): up to 100,000 h
- Lifetime (L80/B10): up to 89,000 h
- Initial color consistency: 3 SDCM

TECHNICAL DATA

Electrical data

Nominal wattage	9.00 W
Nominal voltage	80...86 V
Mains frequency	0 Hz
Protection class	I

Photometrical data

Luminous flux	1128 lm
Luminous efficacy	137 lm/W
Color temperature	3000...4000 K
Light color (designation)	Warm White / Cool White
Color rendering index Ra	> 90
Standard deviation of color matching	3 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG1
Beam angle	115 °

Dimensions & Weight

Length	849.00 mm
Width	24.50 mm
Height	10.50 mm
Product weight	170.00 g

Materials & Colors

Housing color	White
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-40...+80 °C
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h <sup>1)</sup>
---------------------------	------------------------


Lifespan L80/B10 at 25 °C	89000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	100000 h
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE / ENEC / EAC
-----------	-----------------

### DOWNLOAD DATA

Documents and certificates		Document name
	Declarations of conformity	OFFICE LINEAR

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854252365	Folding box 1	60 mm x 1,000 mm	176.00 g	
4099854252372	Shipping box 40	912 mm x 207 mm x 204 mm	8467.00 g	38.51 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.