

# PRODUCT DATASHEET DR ZIGBEE NF P 45W 220-240V 1A2

LED DRIVER ZIGBEE DIRECT PERFORMANCE | Compact constant LED driver with Zigbee dimming interface



#### Areas of application

- Luminaires of protection class I and II
- Indoor SELV installations
- Suitable for LED T5 FC EXTERNAL P
- Emergency lighting systems (DC capable)
- Cove lighting
- Offices
- Education
- Storage areas
- Retail

#### **Product benefits**

- Zigbee 3.0 and Zigbee Direct via Bluetooth Low Energy (BLE)
- Flexible NFC current settings on device in 1 mA steps
- Consumption and diagnostic data via Zigbee
- Low flickering enables high light quality as well as good visual comfort
- High-quality dimming of 1...100 %
- Toolless installation

#### Product features

- Available with an output current range: from 200...750 mA (30 W)
- Available with an output current range: from 600...1,200 mA (45 W)
- Type of installation: independent and built-in
- Suitable for emergency lighting fixtures acc. to EN 60598-2-2 with via NFC adjustable emergency output factor (EOFI)
- Quick and easy current setting via NFC
- Very long lifetime: up to 100,000 h
- Supply voltage: 220...240 V
- Operated with Safety extra-low voltage (SELV): < 60 V

# **TECHNICAL DATA**

# Electrical data

Nominal output power	45 W
Nominal voltage	220240 V
Nominal output voltage	1052 V
Input voltage AC	198264 V <sup>1)</sup>
Input voltage DC	178280 V
U-OUT (working voltage)	1052 V
Type of current	DC
Nominal current	260 mA
Nominal output current	6001200 mA <sup>2)</sup>
Inrush current	5.24 A
Output current tolerance	+/- 3 %
Output ripple current (120 Hz)	+/- 3.0 %
Mains frequency	0/50/60 Hz
Total harmonic distortion	< 7 % <sup>3)</sup>
Power factor $\lambda$	≥0.97 <sup>3)</sup>
ECG efficiency	≥ 90 %
Device power loss	< 5 W
Max. ECG no. on circuit breaker 10 A (B)	34
Max. ECG no. on circuit breaker 16 A (B)	55
Max. ECG no. on circuit breaker 25 A (B)	87
Max. ECG no. on circuit breaker 32 A (B)	111
Max. ECG no. on circuit breaker 10 A (C)	34
Max. ECG no. on circuit breaker 16 A (C)	55
Max. ECG no. on circuit breaker 25 A (C)	87
Max. ECG no. on circuit breaker 32 A (C)	111
Surge capability (L/N-Ground)	2 kV
Surge capability (L-N)	1 kV
Galvanic isolation	SELV
Operating frequency	0/50/60 Hz
Power loss in stand-by mode	≤0.3 W

<sup>1)</sup> Permitted voltage range

# Dimensions & Weight

<sup>2)</sup> Tunable at 1 mA steps, +/- 3 % at full load

<sup>3)</sup> Full load at 230 V/50 Hz



Length	118.20 mm
Mounting hole spacing, length	109 mm
Width	45.00 mm
Height	25.00 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup>
Cable cross-section, output side	0.51.5 mm <sup>2</sup>
Prewired	No
Wire preparation length, input side	67 mm
Wire preparation length, output side	67 mm
Product weight	186.3 g

# Colors & materials

Product color	White
Casing material	Plastic
Body material	Plastic

# Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at to test point	85 °C
Max.housing temperature in case of fault	<110 °C
Temperature range in operation	-20+50 °C
Permitted rel. humidity during operation	585 %

# Lifespan

ECG lifetime	100000 h <sup>1)</sup>
Number of switching cycles	50000

<sup>1)</sup> At Tc max. - 10°C

# Additional product data

Encapsulated	Yes

# Capabilities

Dimmable	Yes
Dimming interface	Zigbee 3.0 <sup>1)</sup>
Dimming range	1100 %

Overheating protection	Yes
Overload protection	Yes
No-load proof	Yes
Short-circuit protection	Yes
Max. cable length to lamp/LED module	0,8 m
Suitable for fixtures with prot. class	II
Suitable for emergency lighting	Yes
Type of connection, output side	Push terminal

<sup>1)</sup> Zigbee Direct via Bluetooth Low Energy (BLE)

# Certificates & Standards

Approval marks – approval	CE / UKCA / EAC / ENEC / EL
Standards	Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 62384
Protection class	II
Type of protection	IP20

# LOGISTICAL DATA

Temperature range at storage	-40+85 °C
------------------------------	-----------

# **EQUIPMENT / ACCESSORIES**

- Cable clamps included for trade types

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Disconnect mains before installation.
- Do not open enclosure-housing.

# DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	DR ZB NF P
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety insert G11226371 24
PDF	Legal information	Legal Insert G11245230 LN T

	Documents and certificates	Document name
PDF	Declarations of conformity	LED DRIVER ZIGBEE
PDF	Declarations of conformity UKCA	LED DRIVER ZIGBEE
PDF	EU Data Act	Field Assistant - NFC Progam Application

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854668678	Folding box	187 mm x 54 mm x 34 mm	201.00 g	0.34 dm <sup>3</sup>
4099854668685	Shipping box 20	282 mm x 205 mm x 177 mm	4326.00 g	10.23 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.