

# PRODUCT DATASHEET LED TUBE T8 EM VALUE 438 mm 5.4W 840

LED TUBE T8 EM VALUE | Economic LED tubes for electromagnetic control gear (CCG) and AC mains



#### Areas of application

- General illumination within ambient temperatures from -20...+45  $^{\circ}\text{C}$
- Corridors, stairways, parking garages
- Warehouses
- Cooling and storage rooms
- Domestic applications

#### Product benefits

- Energy savings of up to 69 % (compared to T8 fluorescent lamp)
- Quick, simple and safe replacement with or without rewiring
- No bending thanks to glass technology
- Very high resistance to switching loads
- Instant-on light, therefore ideally suitable in combination with sensor technology
- Also suitable for operation at low temperatures

#### Product features

- LED replacement for classic T8 fluorescent lamps with G13 socket for use in CCG luminaires or on AC mains
- Single and tandem operation on conventional control gear (≤ 0.9 m versions)
- Tube made of glass
- Long lifetime up to 50,000 h
- Uniform illumination
- Mercury-free and RoHS compliant
- Type of protection: IP20





- Low flicker according to EU 2019-2020 (SVM  $\leq 0.4$  / PstLM  $\leq$  1)

# TECHNICAL DATA


# Electrical data

Nominal wattage	5.4 W
Nominal voltage	220240 V
Operating mode	CCG, AC Mains
Nominal current	25 mA
Type of current	AC
Inrush current	8 A
Suitable for DC input	Yes
Input voltage DC	186260 V
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz <sup>1)</sup>
Max. lamp number on MCB B10 A	75
Max. lamp number on MCB B10 A - CCG without compensation	88
Max. lamp number on MCB B10 A - CCG with compensation	31
Max. lamp number on MCB B16 A	94
Max. lamp number on MCB B16 A - CCG without compensation	110
Max. lamp number on MCB B16 A - CCG with compensation	40
Total harmonic distortion	< 30 %
Power factor $\lambda$	0.90

<sup>1) &</sup>lt;sub>DC 0 Hz</sub>

#### Photometrical data

Luminous flux	650 lm
Luminous efficacy	120 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4



EPREL data spectral diagram PROF LEDr 4000K

# Light technical data

Beam angle	190°	
Warm-up time (60 %)	< 0.50 s	
Starting time	< 0.5 s	

# Dimensions & Weight



Overall length	451.00 mm
Length with base excl. base pins/connection	438.00 mm
Diameter	26.70 mm
Product weight	75.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C <sup>1)</sup>
Maximum temperature at tc test point	70 °C
Performance temp. acc. to IEC 62717	65 °C <sup>2)</sup>

<sup>1)</sup> Temperature surrounding the lamp - for enclosed luminaires: temperature inside of the luminaire

# Lifespan

Lifespan L70/B50 at 25 °C	50000 h
Number of switching cycles	200000
Lumen maintenance at end of service lifetime	0.70

<sup>2)</sup>  $\ensuremath{\mathsf{Tp}}$  rated.  $\ensuremath{\mathsf{Tp}}$  point coincides with  $\ensuremath{\mathsf{Tc}}$  point - marked on device

Rated lamp survival factor at 6,000 h	≥ 0.90
Additional product data	
Additional product data	
Base (standard designation)	G13
Mercury content	0.0 mg
Mercury-free	Yes
Capabilities	
Dimmable	No
Certificates & Standards	
Energy efficiency class	E 1)
Energy consumption	6.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC / UKCA
Photobiological safety group acc. to EN62778	RG0
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (locuntry-specific categorizations	
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo	
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo	
Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo     Country-specific categorizations	west efficiency)
Discreption of the property o	west efficiency)
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lo  Country-specific categorizations  Order reference  LOGISTICAL DATA	west efficiency)  LEDTUBE T8 EM V
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage	west efficiency)  LEDTUBE T8 EM V
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015	west efficiency)  LEDTUBE T8 EM V  -20+80 °C
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used	west efficiency)  LEDTUBE T8 EM V  -20+80 °C
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional	west efficiency)  LEDTUBE T8 EM V  -20+80 °C  LED  NDLS
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  OGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains	LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)	LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)	LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13  No
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source	west efficiency)  LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13  No  No
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope	west efficiency)  LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  OGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source	west efficiency)  LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No  No  No
1) Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (local Country-specific categorizations  Order reference  LOGISTICAL DATA  Temperature range at storage  Energy labelling regulation data acc EU 2019/2015  Lighting technology used  Non-directional or directional  Mains or non-mains  Light source cap-type (or other electric interface)  Connected light source (CLS)  Color-tuneable light source  Envelope  High luminance light source  Anti-glare shield	west efficiency)  LEDTUBE T8 EM V  -20+80 °C  LED  NDLS  MLS  G13  No  No  No  No  No  No  No  No  No  N

Length	451.00 mm
Height	26.70 mm
Width	26.70 mm
Chromaticity coordinate x	0.38
Chromaticity coordinate y	0.38
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	0.9
LED light source replaces a fluorescent light source	No
EPREL ID	2153801
Model number	AC69476

#### **EQUIPMENT / ACCESSORIES**

- Suitable for operation with low-loss and conventional control gears

# Safety advice

- Not suitable for operation with electronic control gear.
- Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.
- Not suitable for emergency lighting.
- Disconnect mains before installation.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	User instruction / safety instructions	
PDF	Extended installation guide	Installation instructions LED TUBE T8, T5 und DULUX LED 2024 10 EN
PDF	Extended installation guide	Notes on the operation of LEDVANCE LED tubes in compensated luminaires
PDF	Extended installation guide	LEDVANCE Luminaire conversion checklist
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Declarations of conformity	LED tube


	Decuments and southester	Decument name	
	Documents and certificates	Document name	
PDF	Declarations of conformity UKCA	LED Tube	
PDF	Certificates	LEDTUBE T8 EM V 438 5.4W	
	Photometric and lighting design files	Document name	
	IES file (IES)	LEDTUBE T8 EM V 438 5.4W 840 LEDV	
	LDT file (Eulumdat)	LEDTUBE T8 EM V 438 5.4W 840 LEDV	
	UGR file (UGR table)	LEDTUBE T8 EM V 438 5.4W 840 LEDV	
	Light distribution curve type polar	LEDTUBE T8 EM V 438 5.4W 840 LEDV	
	Spectral power distribution	EPREL data spectral diagram PROF LEDr 4000K	
-			
	Tender texts	Document name	
	Tender documents	LED TUBE T8 EM VALUE 438 mm 5.4W 840-en	

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854434969	Sleeve 1	495 mm x 28 mm x 28 mm	95.00 g	0.40 dm <sup>3</sup>
4099854434976	Shipping box 10	530 mm x 170 mm x 100 mm	1274.00 g	9.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# ADDITIONAL CATALOG INFORMATION



References / Links

_	For	Guarantee	see www	.ledvance.	.com/	guarantee/
---	-----	-----------	---------	------------	-------	------------

# Legal advice

- When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.