


PRODUCT DATASHEET SP CBO FP RING ADJ ROUND BN

SPOT COMBO FIRE RATED RING ADJUST | Replaceable ring for SPOT COMBO FIRE RATED ADJUST MS in round shape



Product features

- Available in round shape
- Available in 2 different colors: black and brushed nickel
- Material: plastic



TECHNICAL DATA

Dimensions & Weight

| Diameter | 86.00 mm |
|----------------|----------|
| Height | 3 mm |
| Product weight | 16.00 g |



SP CBO FP RING ADJ ROUND BN

Materials & Colors

| Product color | Brushed nickel |
|---------------|----------------|
| Body material | Plastic |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
| Mounting type | Recessed |
| Mounting location | Ceiling |
| Mounting diameter | 86,0 mm |
| Replaceable light source | No |

DOWNLOAD DATA

| Tender texts | Document name |
|------------------|---|
| Tender documents | SPOT COMBO FIRE RATED RING ADJUST ADJ ROUND BN-en |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4099854460173 | BAG 1 | 122 mm x 122 mm x 3 mm | 21.00 g | 0.04 dm ³ |
| 4099854460180 | Shipping box 10 | 180 mm x 129 mm x 129 mm | 347.00 g | 3.00 dm ³ |

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854460197 | Shipping box 200 | 659 mm x 375 mm x 282 mm | 7540.00 g | 69.69 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.