

## PRODUCT DATASHEET

### Decor Corolle Pendant E27 Orange

Decor Corolle | Decorative luminaires made of colorful metal and glass with exchangeable light source



#### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

#### Product benefits

- Allows to create a stylish retro style at home
- Different types of luminaires with the same design language maintain a consistent style at home
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Color matching textile cables

#### Product features

- Housing material: metal and glass
- Textile cable



TECHNICAL DATA

Electrical data


Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Photometrical data

Color rendering index Ra	> 80
--------------------------	------

Dimensions & Weight

Diameter	200.00 mm
Height	1215.00 mm
Product weight	900.00 g



DECOR COROLLE PENDANT E27

Materials & Colors

Product color	Orange
Housing color	Orange
Body material	Steel glass
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)

Type of protection	IP20
Dimmable	No
Mounting type	Suspended
Mounting location	Ceiling
Application environment	Indoor
With light source	No
Replaceable light source	No
Holder designation	E27

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No




### Additional product data

Product remark	Maximum bulb wattage: 25 W (15 W LED)
Number of illuminants	1

### Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire must be disposed of.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

### DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR COROLLE PENDANT E27
	Declarations of conformity	DECOR LUM
	Declarations of conformity UKCA	DECOR LUM COROLLE_SMOKE

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
--------------	------------------------------	--------------------------------------	--------------	--------

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075849129	Folding box 1	222 mm x 222 mm x 257 mm	1312.00 g	12.67 dm <sup>3</sup>
4058075849136	Shipping box 4	460 mm x 460 mm x 279 mm	5913.00 g	59.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.