

PRODUCT DATASHEET

Decor Corolle Wall G9 Orange

Decor Corolle | Decorative luminaires made of colorful metal and glass with exchangeable light source



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Bedrooms

Product benefits

- Color matching metal and textile cables
- Allows to create a stylish retro style at home
- Different types of luminaires with the same design language maintain a consistent style at home
- High flexibility in the choice of the light source
- Sustainable solution thanks to exchangeable light sources
- Easy mounting

Product features

- Housing material: metal and glass
- Textile cable




TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	135.00 mm
Width	210.00 mm
Height	245.00 mm
Product weight	620.00 g



DECOR COROLLE WALL G9

Materials & Colors

Product color	Orange
Housing color	Orange
Body material	Steel glass
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No

Mounting type	Surface
Mounting location	Wall
Application environment	Indoor
With light source	No
Replaceable light source	No
Holder designation	G9

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No


Additional product data

Product remark	Maximum bulb wattage: 20 W (5 W LED) / Available from June 2025
Number of illuminants	1

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The external flexible cable or cord of this luminaire cannot be replaced; if the cord is damaged, the luminaire shall be destroyed.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR COROLLE WALL G9

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075849044	Folding box 1	147 mm x 257 mm x 227 mm	1002.00 g	8.58 dm ³
4058075849051	Shipping box 4	530 mm x 310 mm x 249 mm	4258.00 g	40.91 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.