

PRODUCT DATASHEET SENSOR DIRECT CEILING MOUNTING KIT

SENSOR DIRECT ACCESSORIES | Adapter for surface mounting installations



Areas of application

- Open office spaces
- Meeting, storage and break rooms
- Classrooms
- Stairways

Product features

- Enables surface or recessed ceiling mounting

TECHNICAL DATA

Electrical data

Dimensions & Weight



Length	87.00 mm
Width	87.00 mm
Height	45.00 mm
Diameter	75.00 mm
Product weight	50.00 g

Colors & materials

Product color	White
Body material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-40+70 °C
Temperature range in operation	-40+70 °C

Additional product data

Product remark	Available from September 2025

Capabilities

Dimmable	No
Type of installation	Surface mounting

Certificates & Standards

Protection class	

LOGISTICAL DATA

Temperature range at storage	-40+70 °C
	-

Safety advice

- All electrical connections must be made by a qualified person.

- Caution, risk of electric shock.

DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	SENSOR DIRECT LS-PD-7 IR CI ZB
PDF	Legal information	Informationstext 18 Abs 4 ElektroG
PDF	Legal information	Safety Insert MCU SELECT DIRECT AND SENSOR DIRECT
PDF	Legal information	App Download guide

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854485770	Folding box 1	100 mm x 60 mm x 100 mm	67.00 g	0.60 dm ³
4099854485787	Shipping box 10	320 mm x 220 mm x 125 mm	987.00 g	8.80 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For current information see www.ledvance.com/light-management-systems

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.