

PRODUCT DATASHEET

Endura Classic Erda Wall E27 IP54 Dark Grey

Endura Classic Erda | Dark grey aluminum wall luminaire with E27 socket and globe-shaped diffuser, great for entrances



Areas of application

- Outdoor
- Entrance lighting
- Patios, balconies
- General illumination
- Facade and building illumination

Product benefits

- High flexibility in the choice of the light source thanks to E27 base
- Easy and quick installation

Product features

- Suitable for smart applications thanks to compatibility with SMART+ lamps
- Type of protection: IP54
- Housing material: aluminum
- Diffuser made of opal polycarbonate




TECHNICAL DATA

Electrical data

Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Protection class	I
Operating mode	Mains voltage

Dimensions & Weight

Length	200.00 mm
Width	270.00 mm
Height	250.00 mm
Product weight	800.00 g



ENDURA CLA ERDA W E27 IP54
DG

Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP54
Protection class IK (shock resistance)	IK06
Dimmable	No

Mounting type	Surface
Application environment	Outdoor
With light source	No
Replaceable light source	No
Holder designation	E27

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Maximum bulb wattage: 40W (15W LED) / Available from June 2025
Number of illuminants	1





EQUIPMENT / ACCESSORIES


- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	Endura Classic Erda
	Legal information	Informationstext 18 Abs 4 ElektroG
	Legal information	Safety insert G11219578
	Declarations of conformity	CE Declaration Endura Style Classic IP54

Documents and certificates	Document name
 Declarations of conformity UKCA	UKCA Declaration Endura Classic IP54

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854415616	Folding box 1	206 mm x 238 mm x 283 mm	1030.00 g	13.87 dm ³
4099854415623	Shipping box 4	430 mm x 255 mm x 590 mm	5153.00 g	64.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.