

PRODUCT DATASHEET

SMART+ MATTER Classic A100 14W

827...865 TW E27 SINGLE PACK

SMART+ MATTER CLASSIC shapes Tunable white | Classic bulb shapes with Matter technology Tunable white



Areas of application

- General illumination through smart home technology
- Professional applications (hotels, bars, boutiques etc.) utilizing dynamic and robust ambient lighting effects
- When users want to mix and match smart home products from different manufacturers
- Outdoor use in suitable outdoor luminaires only

Product benefits

- Wireless control via app or voice control
- Seamless integration with Matter-compatible systems
- Simplified set up process due to the standard user-friendly installation steps
- Enhanced security by implementing strong encryption and authentication protocols
- Lower energy consumption than incandescent or halogen lamps

Product features

- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0) or any other Matter-compatible platforms
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Network protocol: Matter over WiFi
- Lifetime: up to 20,000 h
- Compatible with Alexa, Google Home, Apple Home and other Matter-compatible platforms




TECHNICAL DATA

Electrical data

Nominal wattage	14 W
Construction wattage	14.00 W
Nominal voltage	220...240 V
Nominal current	115 mA
Operating frequency	50...60 Hz
Mains frequency	50...60 Hz
Power factor λ	0.50
Claimed equiv. conventional lamp power	100 W
Operating mode	AC Mains

Photometrical data

Light color (designation)	Tunable White
Lumen main.fact.at end of nom.life time	0.95
Standard deviation of color matching	≤ 6 sdc _m
Nominal luminous flux	1521 lm
Luminous flux	1521 lm
Luminous efficacy	108 lm/W
Adjustable color temperature	2700...6500 K
Color temperature	2700...6500 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1
Stroboscope effect metric (SVM)	0.4




Everlight 67-22ST-KK3C 2700K

Light technical data

Beam angle	200 °
------------	-------

Starting time	0.5 s
Warm-up time (60 %)	0.50 s

Dimensions & Weight



Product weight	58.00 g
Diameter	70.00 mm
Maximum diameter	70 mm
Length	137.00 mm
Width	70.00 mm
Height	70.00 mm
Outer bulb [PICOS]	A70

Lifespan

Number of switching cycles	100000
Lifespan	20000 h
Lumen maintenance at end of service lifetime	0.95

Colors & materials

Product color	White
Housing color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

Capabilities

Dimmable	Yes ¹⁾
Compatible smart home technology	Amazon Alexa / Google Assistant / Apple HomeKit / Samsung SmartThings

¹⁾ Via App

Certificates & Standards

Energy efficiency class	F ¹⁾
Energy consumption	14.00 kWh/1000h
Standards	CE / UKCA
Type of protection	IP20

¹⁾ Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

Energy labelling regulation data acc EU 2019/2015





Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	Yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	RANGE
Standby power	0 W
Networked standby power for CLS	<0.5 W
Claim of equivalent power	Yes
Chromaticity coordinate x	0.4578
Chromaticity coordinate y	0.4101

R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.9
Displacement factor	>0.7
LED light source replaces a fluorescent light source	No
EPREL ID	2240732
Model number	AC73907,AC73907

Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

DOWNLOAD DATA

Documents and certificates		Document name
	Extended installation guide	SMTMAT 230V
	Declarations of conformity	SMART MAT
	Declarations of conformity UKCA	
Photometric and lighting design files		Document name
	Spectral power distribution	Everlight 67-22ST-KK3C 2700K

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854528835	Folding box 1	71 mm x 78 mm x 139 mm	88.00 g	0.77 dm ³
4099854528842	Shipping box 4	164 mm x 150 mm x 153 mm	453.00 g	3.76 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.