

PRODUCT DATASHEET

LN INV D 1200 P 40W 940 PS ASY BK

LINEAR INDIVILED DIRECT 1200 PS ASYMMETRIC | Surface mounted luminaire for single or light line office application with CRI90, power select (PS) feature and asymmetric light distribution, 1200 mm



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Offices, education, public buildings
- Single and continuous line configuration
- Direct lighting

Product benefits

- Easy upgradeability of light source and driver (EVERLOOP design)
- High performance with CRI90 and up to 115 lm/W
- Highly versatile due to selectable power steps (Power Select - PS) on the driver
- Asymmetric light distribution for various application areas
- High color consistency with SDCM 3
- Easy installation
- Low flicker light thanks to special electronic control gear
- Multiple mounting options thanks to different accessories

Product features

- Minimalistic LEDVANCE SCALE design in extruded aluminum housing, available in white and black color
- Includes EVERLOOP: Convenient replacement of light source and LED driver
- Linkable into seamless light line with accessories (surface or pendant mounting)
- Pendant mounting with suspension kit (to be ordered separately)




- Glow Wire Test according to IEC 60695-2-12: 850 °C
- 5-pole terminal block, cable cross section up to 5 x 2.5 mm²
- Lifetime (L80/B10): 70,000 h (at 25 °C)

TECHNICAL DATA**Electrical data**

Nominal wattage	40 W / 35 W / 30 W / 25 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	180mA / 165mA / 135mA / 115 mA
Inrush current	15 A
Inrush current time T_{h50}	50 μ s
Max. number of luminaires per miniature circuit breaker B16	50
Max. number of luminaires per miniature circuit breaker C10	36
Max. number of luminaires per miniature circuit breaker C16	58
Power factor λ	> 0.90
Total harmonic distortion	$\leq$ 20 %
Protection class	I
Surge capability (L-N)	1000 V
Surge capability (L/N-Ground)	2000 V
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	4000 lm / 3600 lm / 3100 lm / 2650 lm
Luminous efficacy	100 lm/W / 103 lm/W / 106 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq$ 90
Standard deviation of color matching	3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	$\leq$ 1
Stroboscope effect metric (SVM)	$\leq$ 0.4
Photobiological safety group acc. to EN62778	RG1
Beam angle	55 ° x 55 °
UGR	< 19




LN INV D 1200 P 40W 940 PS ASY
BK 800mA

Adjustable attributes

Nominal wattage	Color temperature	Luminous flux	Luminous efficacy
40 W	4000 K	4000 lm	100 lm/W
35 W	4000 K	3600 lm	103 lm/W
30 W	4000 K	3100 lm	103 lm/W
25 W	4000 K	2650 lm	106 lm/W

Dimensions & Weight

Length	1210.00 mm
Width	125.00 mm
Height	43.00 mm
Product weight	3200.00 g



LN INV 1200 P

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	850 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+50 °C
Temperature range at storage	-20...+80 °C
Type of connection	Screwless terminal
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Ceiling
Application environment	Indoor
Adjustable	No
With light source	Yes
Replaceable light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	100000 h ¹⁾
Lifespan L80/B10 at 25 °C	70000 h ¹⁾
Lifespan L80/B50 at 25 °C	70000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	25000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

Output current	800mA / 700mA / 600mA / 500 mA
ECG - Output ripple current	≤ 5 %
Recommended control gear	OSRAM IT FIT 40/220-240/800 CS L

Certificates & Standards

Standards	CE / CB / ENEC / TÜV SÜD / UKCA / EAC / EPD
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	By the end consumer

Additional product data

Product remark	Available from July 2025
Number of illuminants	1
Added function	EVERLOOP / MULTI SELECT

Accessories Optional

Product image	Product name	EAN
	LN INV SUSPENSION KIT BK	4099854297069
	LN INV SUSPENSION WIRE	4099854323980
	LN INV 1200 THROUGHWIRING KIT	4099854214820
	LN INV INLINE CONNECTOR	4099854215612
	LN INV CORNER CONNECTOR BK	4099854308079
	LN INV INFILL 600 BK	4099854297045
	LN INV INFILL 1200 BK	4099854297007

Product image	Product name	EAN
	LN INV INFILL 1500 BK	4099854297021

EQUIPMENT / ACCESSORIES

- Suspension kit available for pendant luminaire version (to be ordered separately)
- Inline, corner and infill connectors available as separate accessory
- Through-wiring cable kit available

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LN INV
	Addon technical information	LN INV D PS ASY
	Legal information	Safety Insert G11205497
	Legal information	Legal Insert G11235609
	Legal information	Informationstext 18 Abs 4 ElektroG
Photometric and lighting design files		Document name
	IES file (IES)	LN INV D 1200 P 40W 940 PS ASY BK 800mA
	LDT file (Eulumdat)	LN INV D 1200 P 40W 940 PS ASY BK 800mA
	Light distribution curve type polar	LN INV D 1200 P 40W 940 PS ASY BK 800mA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854591716	Folding box 1	178 mm x 1,263 mm x 103 mm	3800.00 g	23.16 dm³
4099854591723	Shipping box 2	1,297 mm x 197 mm x 224 mm	9000.00 g	57.23 dm³

ADDITIONAL CATALOG INFORMATION



UNIV ID 1350 P	OSRAM FT FET 4U	OFF	OFF	=	500	25	2400	114
40W SPS PS AS WT	Z20..344/000 CS L	ON	OFF	=	500	50	3400	153
		ON	OFF	=	750	25	3400	111
		ON	OFF	=	750	50	3400	153
		ON	OFF	=	1000	25	3400	111
		ON	OFF	=	1000	50	3400	153
		ON	OFF	=	1250	25	3600	104
		ON	OFF	=	1250	50	3600	139
		ON	OFF	=	1500	25	3600	104
		ON	OFF	=	1500	50	3600	139
		ON	OFF	=	1750	25	3600	104
		ON	OFF	=	1750	50	3600	139
		ON	OFF	=	2000	25	3600	104
		ON	OFF	=	2000	50	3600	139
		ON	OFF	=	2250	25	3600	104
		ON	OFF	=	2250	50	3600	139
		ON	OFF	=	2500	25	3600	104
		ON	OFF	=	2500	50	3600	139
		ON	OFF	=	2750	25	3600	104
		ON	OFF	=	2750	50	3600	139
		ON	OFF	=	3000	25	3600	104
		ON	OFF	=	3000	50	3600	139
		ON	OFF	=	3250	25	3600	104
		ON	OFF	=	3250	50	3600	139
		ON	OFF	=	3500	25	3600	104
		ON	OFF	=	3500	50	3600	139
		ON	OFF	=	3750	25	3600	104
		ON	OFF	=	3750	50	3600	139
		ON	OFF	=	4000	25	3600	104
		ON	OFF	=	4000	50	3600	139
		ON	OFF	=	4250	25	3600	104
		ON	OFF	=	4250	50	3600	139
		ON	OFF	=	4500	25	3600	104
		ON	OFF	=	4500	50	3600	139
		ON	OFF	=	4750	25	3600	104
		ON	OFF	=	4750	50	3600	139
		ON	OFF	=	5000	25	3600	104
		ON	OFF	=	5000	50	3600	139
		ON	OFF	=	5250	25	3600	104
		ON	OFF	=	5250	50	3600	139
		ON	OFF	=	5500	25	3600	104
		ON	OFF	=	5500	50	3600	139
		ON	OFF	=	5750	25	3600	104
		ON	OFF	=	5750	50	3600	139
		ON	OFF	=	6000	25	3600	104
		ON	OFF	=	6000	50	3600	139
		ON	OFF	=	6250	25	3600	104
		ON	OFF	=	6250	50	3600	139
		ON	OFF	=	6500	25	3600	104
		ON	OFF	=	6500	50	3600	139
		ON	OFF	=	6750	25	3600	104
		ON	OFF	=	6750	50	3600	139
		ON	OFF	=	7000	25	3600	104
		ON	OFF	=	7000	50	3600	139
		ON	OFF	=	7250	25	3600	104
		ON	OFF	=	7250	50	3600	139
		ON	OFF	=	7500	25	3600	104
		ON	OFF	=	7500	50	3600	139
		ON	OFF	=	7750	25	3600	104
		ON	OFF	=	7750	50	3600	139
		ON	OFF	=	8000	25	3600	104
		ON	OFF	=	8000	50	3600	139
		ON	OFF	=	8250	25	3600	104
		ON	OFF	=	8250	50	3600	139
		ON	OFF	=	8500	25	3600	104
		ON	OFF	=	8500	50	3600	139
		ON	OFF	=	8750	25	3600	104
		ON	OFF	=	8750	50	3600	139
		ON	OFF	=	9000	25	3600	104
		ON	OFF	=	9000	50	3600	139
		ON	OFF	=	9250	25	3600	104
		ON	OFF	=	9250	50	3600	139
		ON	OFF	=	9500	25	3600	104
		ON	OFF	=	9500	50	3600	139
		ON	OFF	=	9750	25	3600	104
		ON	OFF	=	9750	50	3600	139
		ON	OFF	=	10000	25	3600	104
		ON	OFF	=	10000	50	3600	139
		ON	OFF	=	10250	25	3600	104
		ON	OFF	=	10250	50	3600	139
		ON	OFF	=	10500	25	3600	104
		ON	OFF	=	10500	50	3600	139
		ON	OFF	=	10750	25	3600	104
		ON	OFF	=	10750	50	3600	139
		ON	OFF	=	11000	25	3600	104
		ON	OFF	=	11000	50	3600	139
		ON	OFF	=	11250	25	3600	104
		ON	OFF	=	11250	50	3600	139
		ON	OFF	=	11500	25	3600	104
		ON	OFF	=	11500	50	3600	139
		ON	OFF	=	11750	25	3600	104
		ON	OFF	=	11750	50	3600	139
		ON	OFF	=	12000	25	3600	104
		ON	OFF	=	12000	50	3600	139
		ON	OFF	=	12250	25	3600	104
		ON	OFF	=	12250	50	3600	139
		ON	OFF	=	12500	25	3600	104
		ON	OFF	=	12500	50	3600	139
		ON	OFF	=	12750	25	3600	104
		ON	OFF	=	12750	50	3600	139
		ON	OFF	=	13000	25	3600	104
		ON	OFF	=	13000	50	3600	139
		ON	OFF	=	13250	25	3600	104
		ON	OFF	=	13250	50	3600	139
		ON	OFF	=	13500	25	3600	104
		ON	OFF	=	13500	50	3600	139
		ON	OFF	=	13750	25	3600	104
		ON	OFF	=	13750	50	3600	139
		ON	OFF	=	14000	25	3600	104
		ON	OFF	=	14000	50	3600	139
		ON	OFF	=	14250	25	3600	104
		ON	OFF	=	14250	50	3600	139
		ON	OFF	=	14500	25	3600	104
		ON	OFF	=	14500	50	3600	139
		ON	OFF	=	14750	25	3600	104
		ON	OFF	=	14750	50	3600	139
		ON	OFF	=	15000	25	3600	104
		ON	OFF	=	15000	50	3600	139
		ON	OFF	=	15250	25	3600	104
		ON	OFF	=	15250	50	3600	139
		ON	OFF	=	15500	25	3600	104
		ON	OFF	=	15500	50	3600	139
		ON	OFF	=	15750	25	3600	104
		ON	OFF	=	15750	50	3600	139
		ON	OFF	=	16000	25	3600	104
		ON	OFF	=	16000	50	3600	139
		ON	OFF	=	16250	25	3600	104
		ON	OFF	=	16250	50	3600	139
		ON	OFF	=	16500	25	3600	104
		ON	OFF	=	16500	50	3600	139
		ON	OFF	=	16750	25	3600	104
		ON	OFF	=	16750	50	3600	139
		ON	OFF	=	17000	25	3600	104
		ON	OFF	=	17000	50	3600	139
		ON	OFF	=	17250	25	3600	104
		ON	OFF	=	17250	50	3600	139
		ON	OFF	=	17500	25	3600	104
		ON	OFF	=	17500	50	3600	139
		ON	OFF	=	17750	25	3600	104
		ON	OFF	=	17750	50	3600	139
		ON	OFF	=	18000	25	3600	104
		ON	OFF	=	18000	50	3600	139
		ON	OFF	=	18250	25	3600	104
		ON	OFF	=	18250	50	3600	139
		ON	OFF	=	18500	25	3600	104
		ON	OFF	=	18500	50	3600	139
		ON	OFF	=	18750	25	3600	104
		ON	OFF	=	18750	50	3600	139
		ON	OFF	=	19000	25	3600	104
		ON	OFF	=	19000	50	3600	139
		ON	OFF	=	19250	25	3600	104
		ON	OFF	=	19250	50	3600	139
		ON	OFF	=	19500	25	3600	104
		ON	OFF	=	19500	50	3600	139
		ON	OFF	=	19750	25	3600	104
		ON	OFF	=	19750	50	3600	139
		ON	OFF	=	20000	25	3600	104
		ON	OFF	=	20000	50	3600	139
		ON	OFF	=	20250	25	3600	104
		ON	OFF	=	20250	50	3600	139
		ON	OFF	=	20500	25	3600	104
		ON	OFF	=	20500	50	3600	139
		ON	OFF	=	20750	25	3600	104
		ON	OFF	=	20750	50	3600	139
		ON	OFF	=	21000	25	3600	104
		ON	OFF	=	21000	50	3600	139
		ON	OFF	=	21250	25	3600	104
		ON	OFF	=	21250	50	3600	139
		ON	OFF	=	21500	25	3600	104
		ON	OFF	=	21500	50	3600	139
		ON	OFF	=	21750	25	3600	104
		ON	OFF	=	21750	50	3600	139
		ON	OFF	=	22000	25	3600	104
		ON	OFF	=	22000	50	3600	139
		ON	OFF	=	22250	25	3600	104
		ON	OFF	=	22250	50	3600	139
		ON	OFF	=	22500	25	3600	104
		ON	OFF	=	22500	50	3600	139
		ON	OFF	=	22750	25	3600	104
		ON	OFF	=	22750	50	3600	139
		ON	OFF	=	23000	25	3600	104
		ON	OFF	=	23000	50	3600	139
		ON	OFF	=	23250	25	3600	104
		ON	OFF	=	23250	50	3600	139
		ON	OFF	=	23500	25	3600	104
		ON	OFF	=	23500	50	3600	139
		ON	OFF	=	23750	25	3600	104
		ON	OFF	=	23750	50	3600	139
		ON	OFF	=	24000	25	3600	104
		ON	OFF	=	24000	50	3600	139
		ON	OFF	=	24250	25	3600	104
		ON	OFF	=	24250	50	3600	139
		ON	OFF	=	24500	25	3600	104
		ON	OFF	=	24500	50	3600	139
		ON	OFF	=	24750	25	3600	104
		ON	OFF	=	24750	50	3600	139
		ON	OFF	=	25000	25	3600	104

– For Guarantee see www.ledvance.com/guarantee

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.