

# PRODUCT DATASHEET

## Essential Orbis IP44 290mm 18W 830 Black

Essential Orbis IP44 | Splash-proof LED ceiling light



---

### Areas of application

- Bathrooms
- Workshops, garages, covered outdoor storage areas
- Living areas (living rooms, dining rooms, bedrooms etc.)

---

### Product benefits

- Long lifetime thanks to LED technology
- Excellent price/performance ratio

---

### Product features

- Type of protection: IP44
- Lifetime up to 30,000 h



---

**TECHNICAL DATA****Electrical data**


Nominal wattage	18.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	165.000 mA
Inrush current	0.165 A
Inrush current time $T_{h50}$	142 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	58
Max. number of luminaires per miniature circuit breaker C10	60
Max. number of luminaires per miniature circuit breaker C16	96
Power factor $\lambda$	0.50
Total harmonic distortion	65 %
Protection class	I
Operating mode	Mains voltage

**Photometrical data**

Luminous flux	1200 lm
Total luminous flux of contained light sources	2000
Luminous efficacy	67 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	6 sdc <sub>m</sub>
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120 °

**Dimensions & Weight**

Diameter	285.00 mm
Height	65.00 mm
Product weight	480.00 g



ORBIS ESSENTIAL 290 18W

### Materials & Colors

Product color	Black
Housing color	Black
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Wall
With light source	Yes
Replaceable light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	15000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Emergency lighting

Type of emergency operation test	None
----------------------------------	------

**Certificates & Standards**

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

**Additional product data**

Product remark	Available from September 2025
----------------	-------------------------------


**EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included

**Safety advice**

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

**DOWNLOAD DATA**

Documents and certificates	Document name
 User instruction / safety instructions	Orbis Essential IP44

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075855021	Folding box 1	73 mm x 308 mm x 310 mm	771.00 g	6.97 dm <sup>3</sup>
4058075855038	Shipping box 6	452 mm x 322 mm x 335 mm	5266.00 g	48.76 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.