

# PRODUCT DATASHEET Essential Panel Square 600x600mm 36W 830 White

Essential Panel Square | Essential Panel Ceilings for easy use



# Areas of application

- Living areas (living rooms, dining rooms, bedrooms etc.)

### Product benefits

- Long lifetime thanks to LED technology
- Excellent price/performance ratio

### **Product features**

- LED ceiling luminaires with aluminum frame
- Color temperature: 3,000 K
- Lifetime up to 25,000 h
- Type of protection: IP20

830 White

# TECHNICAL DATA

# Electrical data


Nominal wattage	36.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz
Nominal current	175 mA
Inrush current	0.175 A
Inrush current time T <sub>h50</sub>	860 µs
Max. number of luminaires per miniature circuit breaker B16	13
Max. number of luminaires per miniature circuit breaker C10	13
Max. number of luminaires per miniature circuit breaker C16	21
Power factor $\lambda$	> 0.9
Total harmonic distortion	20 %
Protection class	II
Operating mode	Mains voltage

# Photometrical data

Luminous flux	3200 lm
Total luminous flux of contained light sources	4300 lm
Luminous efficacy	89 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	110°

# Dimensions & Weight

Length	595.00 mm
Width	60.00 mm
Height	595.00 mm
Product weight	1900.00 g



# Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum Steel
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+70 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Protection class IK (shock resistance)	IK02
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
With light source	Yes
Replaceable light source	No

# Lifespan

Lifespan L70/B50 at 25 °C	25000 h <sup>1)</sup>
Number of switching cycles	12500

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# **Emergency lighting**

Type of emergency operation test None
---------------------------------------

# Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

### Additional product data

Product remark	Available from September 2025
----------------	-------------------------------

### **EQUIPMENT / ACCESSORIES**

- Mounting screws and dowels included

### Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

### **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions Panel Essential Rectangular		
PDF	Declarations of conformity	CE Declaration Panel Essential	
PDF	Declarations of conformity UKCA	UKCA Declaration Panel Essential	

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075854635	Folding box	92 mm x 647 mm x 638 mm	2639.00 g	37.98 dm <sup>3</sup>
4058075854642	Shipping box 4	660 mm x 385 mm x 660 mm	11662.00 g	167.71 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.