

PRODUCT DATASHEET LED Downlight Set IP44 Dim Slim 160mm 18W Metal 830 White

LED Downlight Set IP44 | Recess Downlight IP44



Areas of application

- Bathrooms
- Workshops, garages, covered outdoor storage areas
- Living areas (living rooms, dining rooms, bedrooms etc.)

Product benefits

- Through-wiring possible with included connector box
- Easy mounting

Product features

- Recessed ceiling mounting
- Color temperature: 3,000 K
- Through wiring possible
- Type of protection: IP44

TECHNICAL DATA

Electrical data


Nominal wattage	18.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	140.000 mA
Max. number of luminaires per miniature circuit breaker B16	24
Max. number of luminaires per miniature circuit breaker C16	40
Power factor λ	> 0.70
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	1400 lm
Total luminous flux of contained light sources	1400 lm
Luminous efficacy	77 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdcm
Flickering metric (Pst LM)	<1
Stroboscope effect metric (SVM)	<0.4
Photobiological safety group acc. to EN62778	RG0
Beam angle	120°

Dimensions & Weight

Diameter	160.00 mm
Height	35.00 mm
Product weight	334.00 g



DL SET SLIM170 METAL 830IP44WT 6X3

Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polystyrene (PS)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP44/IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Mounting diameter	135 mm
Mounting depth	35 mm
With light source	Yes
Replaceable light source	No

Lifespan

Number of switching cycles	50000

Emergency lighting

	None
--	------

Certificates & Standards

Standards	CE
Luminaire with limited surface temperature, "D sign"	No
Replaceable light source (EPREL)	Not replaceable

Additional product data

Product remark Available from October 2025
--

Safety advice

- Luminaire must be disconnected from mains during installation, maintenance and cover removal
- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

DOWNLOAD DATA

Documents and certificates		Document name	
PDF	User instruction / safety instructions	DL SET SLIM	
Declarations of conformity CE Declaration Downling		CE Declaration Downlight Metal	
PDF	Declarations of conformity UKCA UKCA Declaration Downlight Metal		

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075854352	Folding box 3	173 mm x 173 mm x 173 mm	1206.00 g	5.18 dm ³
4058075854369	Shipping box 18	536 mm x 366 mm x 197 mm	7925.00 g	38.65 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.