

# PRODUCT DATASHEET LED Spot Cylinder Duo 2xGU10 Brushed Nickel

LED Spot Cylinder Duo | Surface mounted luminaires with adjustable GU10 spotlights

#### Areas of application

- Indoor applications



### Product benefits

- Timeless design
- Flexible thanks to replaceable LED lamps
- Easy mounting

#### **Product features**

- Luminaire family features five versions with up to 6 spot heads
- Housing surface made of brushed and chrome nickel
- Adjustable head
- On/off switch on 1-head version for easy operation




# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	T. Control of the con
Operating mode	Mains voltage

# Dimensions & Weight

Length	364.00 mm
Width	70.00 mm
Height	133.00 mm
Product weight	380.00 g



# Materials & Colors

Product color	Brushed nickel chrome	
Housing color	Brushed nickel chrome	
Body material	Steel	
Glow Wire Test according to IEC 60695-2-12	650 °C	

# Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling
Adjustable	Yes

With light source	No
Replaceable light source	Yes
Holder designation	GU10

## **Emergency lighting**

Type of emergency operation test	None
----------------------------------	------

#### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

## Additional product data

Product remark	Maximum bulb wattage: 5 W LED / Available from January 2026
Number of illuminants	2

### Safety advice

- Check wall-ceiling for suitability. If uncertain, seek professional advice.
- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### DOWNLOAD DATA

	Documents and certificates	Document name
PDF	User instruction / safety instructions	LED SPOT CYLINDER DUO G11239547

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075852686	Folding box 1	82 mm x 112 mm x 376 mm	481.00 g	3.45 dm <sup>3</sup>
4058075852693	Shipping box 4	390 mm x 176 mm x 247 mm	2287.00 g	16.95 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.