

## PRODUCT DATASHEET

# Decor Spot Moon 4Spot Cross 21W 830 Black

Decor Spot Moon | Ceiling mounted luminaires with adjustable spotlights



### Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements

### Product benefits

- High-quality look and feel
- Functional and minimalistic design
- Easy mounting

### Product features

- Luminaire family features five versions with up to 4 spot heads
- Adjustable heads
- Housing material: metal



---

**TECHNICAL DATA****Electrical data**


Nominal wattage	21.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	160.000 mA
Inrush current time $T_{h50}$	260 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	85
Max. number of luminaires per miniature circuit breaker C10	53
Max. number of luminaires per miniature circuit breaker C16	85
Power factor $\lambda$	> 0.5
Total harmonic distortion	66 %
Protection class	I
Operating mode	Mains voltage

**Photometrical data**

Luminous flux	1120 lm
Total luminous flux of contained light sources	2000 lm
Luminous efficacy	53 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	6 sdcn
Photobiological safety group acc. to EN62778	RG1
Beam angle	115 °

**Dimensions & Weight**

Length	482.00 mm
Width	482.00 mm
Height	92.00 mm
Product weight	1100.00 g



DECOR SPOT MOON 4SP CROSS  
21W 830BK

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
With light source	Yes
Replaceable light source	No

Lifespan

Number of switching cycles	15000
----------------------------	-------





Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DECOR SPOT MOON
	Legal information	Safety insert G11219578
	Declarations of conformity	DECOR LUM
	Declarations of conformity UKCA	DECOR LUM

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854472336	Folding box 1	122 mm x 222 mm x 573 mm	1720.00 g	15.52 dm <sup>3</sup>
4099854472343	Shipping box 4	586 mm x 500 mm x 247 mm	6880.00 g	72.37 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.