

PRODUCT DATASHEET

LED Spot GU10 Black 6 X 3.4W 927 DIM

LED Spot Black | Ceiling mounted luminaires with adjustable, dimmable GU10 spotlights



Areas of application

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Kitchens, workspaces
- Ceiling and wall surface mounting

Product benefits

- Timeless design
- High-quality housing with matt white or matt black surface
- Flexible thanks to replaceable LED lamps
- Dimmable OSRAM lamp included
- Easy mounting

Product features

- Luminaire family features five versions with up to 6 spot heads
- Adjustable heads



TECHNICAL DATA

Electrical data


Nominal wattage	20.40 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	102.000 mA
Inrush current time T _{h50}	600 µs
Max. number of luminaires per miniature circuit breaker B16	25
Max. number of luminaires per miniature circuit breaker C16	44
Power factor λ	0.70
Total harmonic distortion	100 %
Protection class	I
Operating mode	Mains voltage

Photometrical data

Luminous flux	1380 lm
Total luminous flux of contained light sources	1380 lm
Luminous efficacy	68 lm/W
Color temperature	2700 K
Light color (designation)	Warm White
Color rendering index Ra	90
Standard deviation of color matching	≤5 sdc _m
Photobiological safety group acc. to EN62778	RG1
Beam angle	36 °

Dimensions & Weight

Length	1198.00 mm
Width	90.00 mm
Height	176.00 mm
Product weight	1310.00 g



LED SPOT 6X3.4W 927 GU10

Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP20
Protection class IK (shock resistance)	IK06
Dimmable	Yes
Mounting type	Surface
Adjustable	Yes
With light source	Yes
Replaceable light source	No
Holder designation	GU10

Lifespan

Lifespan L70/B50 at 25 °C	25000 h ¹⁾
Number of switching cycles	100000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Maximum bulb wattage: 5 W LED
Number of illuminants	6






EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	LED SPOT GU10
	User instruction / safety instructions	LED SPOT GU10
	Legal information	Safety insert G11219578
	Declarations of conformity	CE Declaration LED SPOT
	Declarations of conformity UKCA	UKCA Declaration LED SPOT

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854474514	Folding box 1	130 mm x 175 mm x 440 mm	1470.00 g	10.01 dm ³
4099854474521	Shipping box 4	450 mm x 280 mm x 380 mm	6572.00 g	47.88 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.