

PRODUCT DATASHEET

Office Line Cuboid Ceiling 30W 840 DIM Black

Office Line cuboid ceiling | Office ceiling luminaire with 3-step-dim



Areas of application

- Office lighting
- Indoor applications
- Home offices
- General indoor illumination
- Kitchens, workspaces

Product benefits

- Linear luminaire in timeless design
- 3 step dimming via switch on top of the luminaire
- High quality metal housing

Product features

- Lifetime up to 100,000 h
- Color temperature: 4,000 K
- Material: Aluminium (Housing), Polycarbonate (Diffuser)



TECHNICAL DATA

Electrical data


| | |
|---|---------------|
| Nominal wattage | 30.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 136.000 mA |
| Inrush current time T _{h50} | 153.8 µs |
| Max. number of luminaires per miniature circuit breaker B16 | 24 |
| Max. number of luminaires per miniature circuit breaker C10 | 25 |
| Max. number of luminaires per miniature circuit breaker C16 | 40 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | I |
| Operating mode | Mains voltage |

Photometrical data

| | |
|--|------------|
| Luminous flux | 3100 lm |
| Total luminous flux of contained light sources | 4200 lm |
| Luminous efficacy | 100 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | 6 sdcn |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 105 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1126.00 mm |
| Width | 41.00 mm |
| Height | 70.00 mm |
| Product weight | 1270.00 g |



Materials & Colors

| | |
|-----------------|--------------------|
| Product color | Black |
| Housing color | Black |
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|-----------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK03 |
| Dimmable | Yes |
| Type of dimming | 3 DIM |
| Mounting type | Surface |
| With light source | Yes |
| Replaceable light source | No |

Lifespan

| | |
|----------------------------|------------------------|
| Lifespan L70/B50 at 25 °C | 100000 h ¹⁾ |
| Number of switching cycles | 50000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| | |
|--|-----------------|
| Standards | CE / UKCA / EAC |
| Luminaire with limited surface temperature, "D sign" | No |

Ball shot safe

No





EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- The luminaires are not suitable for covering with thermally insulated material.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.
- Check wall-ceiling for suitability. If uncertain, seek professional advice.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|-------------------------|
|  | User instruction / safety instructions | OFFICE LINE CUBOID |
|  | Legal information | Safety insert G11222027 |
|  | Declarations of conformity | OFFICE LINE CUBOID |
|  | Declarations of conformity UKCA | OFFICE LINE CUBOID |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854464775 | Folding box 1 | 101 mm x 71 mm x 1,184 mm | 2165.00 g | 8.49 dm ³ |
| 4099854464782 | Shipping box 4 | 1,285 mm x 240 mm x 180 mm | 8660.00 g | 55.51 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.