

# PRODUCT DATASHEET ENDURA® Classic Hagen 50 cm Sensor E27 IP44 Dark Grey

ENDURA® Classic Hagen | Aluminum lantern-style wall and bollard luminaires with nordic design, glass cover, E27 socket and option with movement detection and daylight sensor



# Areas of application

- Outdoor
- Entrance lighting
- Patios, balconies
- General illumination
- Facade and building illumination
- Pathway lighting

### **Product benefits**

- High flexibility in the choice of the light source thanks to E27 socket
- Easy and quick installation
- Option with PIR motion detection and daylight sensor, matching with housing color available
- Long-term energy and cost savings (sensor version)

### **Product features**

- Suitable for smart applications thanks to compatibility with SMART+ lamps
- Lower light smog, on-demand lighting (sensor version)
- Direct illumination
- Die-cast aluminum housing
- Anthracite housing color
- Glass diffuser



- Type of protection: IP44


# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	50 Hz
Protection class	1
Operating mode	Mains voltage

# Dimensions & Weight

Diameter	120.00 mm
Height	500.00 mm
Product weight	1655.00 g



ENDURA CLA HAGEN 50 S E27 IP44 DG

# Materials & Colors

Product color	Dark grey
Housing color	Dark grey
Body material	Aluminum
Cover material	Glass
Glow Wire Test according to IEC 60695-2-12	650 °C

# **Application & Mounting**

Ambient temperature range	-20+45 °C
Temperature range at storage	-20+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44/IP44
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ground
Application environment	Outdoor
With light source	No
Replaceable light source	No
Holder designation	E27

## Sensor

Type of sensor	Motion	
Sensor technology	Passive infrared (PIR)	
Sensor detection angle	120 °	
Sensor controlled switching time	60 s	
Detection range of motion sensor	68 m	
Detection threshold of daylight sensor	20 lx	

## Certificates & Standards

Standards	CE / UKCA
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable

# Additional product data

Product remark	Maximum bulb wattage: 40 W
Number of illuminants	1

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

# Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.

## DOWNLOAD DATA

Documents and certificates		Document name	
POF	User instruction / safety instructions	ENDURA CLASSIC HAGEN	
POF	Legal information	Safety insert G11219578	

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854709661	Folding box 1	147 mm x 236 mm x 544 mm	1948.00 g	18.87 dm <sup>3</sup>
4099854709678	Shipping box 4	585 mm x 255 mm x 570 mm	8880.00 g	85.03 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.