

# PRODUCT DATASHEET ENDURA Classic Cube Adjustable Wall Silver

ENDURA® Classic Cube ADJ Wall | Outdoor Endura Classic Cube with socket GU10



#### Areas of application

- Entrance lighting
- Patios, balconies
- Building facades

## Product benefits

- High flexibility in the choice of the light source thanks to GU10 socket
- Easy and quick installation
- High-quality materials

## **Product features**

- Die-cast aluminum housing
- Adjustable luminaire head



# TECHNICAL DATA

# Electrical data

Nominal voltage	220240 V
Mains frequency	5060 Hz
Protection class	l .

# Dimensions & Weight

Length	66.00 mm
Width	93.00 mm
Height	100.00 mm
Product weight	500.00 g



## Materials & Colors

Product color	Silver
Housing color	Silver
Body material	Aluminum
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
Adjustable	Yes
With light source	No

Replaceable light source	No
Holder designation	GU10

## Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

## Additional product data

Product remark	Maximum bulb wattage: 35 W
Number of illuminants	1

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

## Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

## **DOWNLOAD DATA**

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	nstructions ENDURA CLASSIC CUBE ADJ WALL	
PDF	Legal information	Safety insert G11219578	
POF	Declarations of conformity	ENDURA CLASSIC	
POF	Declarations of conformity UKCA	Fixed LUM without EMC	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854446252	Folding box	82 mm x 112 mm x 122 mm	566.00 g	1.12 dm <sup>3</sup>
4099854446269	Shipping box	263 mm x 130 mm x 272 mm	3635.00 g	9.30 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.