

PRODUCT DATASHEET

Endura Classic Angela Wall E27 IP54 Dark Grey

ENDURA® Classic Amber | Bollard and wall luminaires with dark grey stainless steel and aluminum housing and E27 socket



Areas of application

- Outdoor
- Entrance lighting
- Patios, balconies
- General illumination
- Facade and building illumination

Product benefits

- High flexibility in the choice of the light source thanks to E27 base
- Easy and quick installation

Product features

- Suitable for smart applications thanks to compatibility with SMART+ lamps
- Type of protection: IP54
- Housing material: aluminum
- Diffuser made of opal polycarbonate




TECHNICAL DATA

Electrical data

| | |
|------------------|---------------|
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Protection class | I |
| Operating mode | Mains voltage |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 250.00 mm |
| Width | 140.00 mm |
| Height | 148.00 mm |
| Product weight | 1100.00 g |



ENDURA CLA ANGELA W E27 IP54
DG

Materials & Colors

| | |
|--|--------------------|
| Product color | Dark gray |
| Housing color | Dark gray |
| Body material | Aluminum |
| Cover material | Polycarbonate (PC) |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |

Application & Mounting

| | |
|--|-----------------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Terminal, 3-Pole (L, N, PE) |
| Type of protection | IP54 |
| Protection class IK (shock resistance) | IK06 |
| Dimmable | No |
| Mounting type | Surface |

| | |
|--------------------------|---------|
| Application environment | Outdoor |
| With light source | No |
| Replaceable light source | No |
| Holder designation | E27 |

Certificates & Standards

| | |
|--|-----------|
| Standards | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No |
| Ball shot safe | No |

Additional product data

| | |
|-----------------------|--|
| Product remark | Maximum bulb wattage: 40W (15W LED) / Available from June 2025 |
| Number of illuminants | 1 |






EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

Safety advice

- All electrical connections must be made by a qualified person.
- Caution, risk of electric shock.
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|--|--|--|
|  | User instruction / safety instructions | Endura Classic Angela |
|  | Legal information | Informationstext 18 Abs 4 ElektroG |
|  | Legal information | Safety insert G11219578 |
|  | Declarations of conformity | CE Declaration Endura Style Classic IP54 |
|  | Declarations of conformity UKCA | UKCA Declaration Endura Classic IP54 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4099854415593 | Folding box 1 | 157 mm x 262 mm x 158 mm | 1241.00 g | 6.50 dm ³ |
| 4099854415609 | Shipping box 4 | 325 mm x 280 mm x 345 mm | 5649.00 g | 31.40 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.