

PRODUCT DATASHEET SMART+ ZB FLEX 3P RGB + TW

SMART+ Flex RGBW | Flexible LED strips for indoor use with Zigbee technology

Areas of application

- General illumination



Product benefits

- Splittable in three parts and extendable with SMART+ FLEX 2P EXTENSION
- Easy to install and use

Product features

- Flexible, self-adhesive RGBW strip with wireless smart lighting function
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 2,000...6,500 K
- Dimmable
- Network protocol: ZigBee
- Lifetime: up to 20,000 h
- Controllable via compatible smart home system (gateway and app) or SMART+ Switch
- For full functionality, connection to a compatible smart home System (gateway and app) required



- Extendable up to 5 meters
- Controllable via SMART+ App (with minimum Android 8.0 or iOS 14.0)

TECHNICAL DATA

Electrical data

Nominal wattage	11.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Nominal current	68.000 mA
Power factor λ	> 0.5
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	700 lm
Total luminous flux of contained light sources	920 lm
Luminous efficacy	64 lm/W
Color temperature	20006500 K
Light color (designation)	RGBW
Color rendering index Ra	80
Beam angle	120 °

Dimensions & Weight

Length	1800.00 mm
Width	12.00 mm
Height	3.00 mm
Product weight	340.00 g



Materials & Colors

Product color	Transparent
Housing color	White
Body material	Plastic

Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Temperature range at storage	-20+85 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	Yes
Mounting type	Surface
Mounting location	All surfaces
Application environment	Indoor
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	20000 h
Number of switching cycles	1000000

Certificates & Standards

Standards	CE
Replaceable light source (EPREL)	Not replaceable

Additional product data

EQUIPMENT / ACCESSORIES

- Control via app requires LIGHTIFY system (app and gateway) or other compatible Smart home system
- Power supply included (except extension version of product)
- For control via SMART+ App, a smartphone or tablet is required (with minimum Android 8.0 or iOS 14.0)

Safety advice

- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by a qualified person in order to avoid a hazard.
- To reduce the risk of strangulation the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.
- Do not connect the rope light to the supply while it is wound onto a reel. Do not use the lightstrip when covered or recessed into a surface. The string of lights may not be operated within the packaging. Do not open the lightstrip.

DOWNLOAD DATA

	Documents and certificates	Document name	
POF	User instruction / safety instructions	UI_SMART ZB FLEX 3P MULTICOLOR	
PDF	Legal information	Web UI Insert SMART FLEX	
POF	Legal information	Legal insert residential luminaires	
POF	Declarations of conformity	Declaration of Conformity Smart Home	
PDF	EU Data Act	SMART ZigBee Lamps and Luminaires	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075208339	Folding box 1	61 mm x 190 mm x 154 mm	465.00 g	1.78 dm ³
4058075212787	Shipping box 4	327 mm x 202 mm x 138 mm	2010.00 g	9.12 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- Further information and frequently asked questions (FAQs) at www.ledvance.com/consumer/smart/faq

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.