

# PRODUCT DATASHEET SMART+ ZB PLUG UK

SMART+ plugs with Zigbee technology | Plug with smart socket to control non smart devices with ZigBee technology



## Areas of application

 Wherever non-smart devices need to be integrated into compatible smart home systems

## **Product benefits**

- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Simple connection of electric devices via standard socket

#### **Product features**

- Control via compatible smart home system or on/off button on the device
- High switching power: up to 3,680 W / 16 A
- Functionality depends on used type of control
- Network protocol: ZigBee 3.0




## **TECHNICAL DATA**

## Electrical data

Nominal voltage	240 V
1 Voltage	240 V

# Dimensions & Weight



Product weight	103.00 g
Length	63.0 mm
Width	58.5 mm
Height	58.5 mm

## Lifespan

Number of switching cycles	25000
----------------------------	-------

## Colors & materials

Product color	White

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C

# Additional product data

	High switching power: up to 2,990 W / 13 A / Reset settings to default by switching the product on for five seconds and off for five seconds	
Product remark	and repeating this five times. / Alternatively, press the reset button once for ten seconds.	

# Capabilities

Compatible smart home technology	Philips Hue / Amazon Alexa / Google Assistant

## Certificates & Standards

Standards	CE
Protection class	П
Type of protection	IP20

#### **EQUIPMENT / ACCESSORIES**

- Control via app requires a compatible Smart home system

## Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (for UK max. 13 A and for EU max. 16 A)
- Product in protection class I. All electrically conductive, metallic housing parts that can absorb voltage during operation or during maintenance in the event of a fault must be continuously connected to the protective earthing conductor.

#### **DOWNLOAD DATA**

Documents and certificates Docume		Document name
POF	User instruction / safety instructions	Web UI SMART Plug Zigbee UK
POF	Declarations of conformity	SMART ZB PLUG UK
PDF	Declarations of conformity UKCA	SMART ZB PLUG UK

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075208322	Folding box	61 mm x 96 mm x 154 mm	199.00 g	0.90 dm <sup>3</sup>
4058075212879	Shipping box 4	211 mm x 167 mm x 141 mm	917.00 g	4.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.