

# PRODUCT DATASHEET P PAR 38 120 30 ° 12 W/6500 K E27

PARATHOM® PAR38 | LED reflector lamps PAR38 with retrofit screw base



#### Areas of application

- Shops and exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Quick, simple and safe replacement without rewiring
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Low maintenance costs thanks to long lifetime
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Lower energy consumption than incandescent or halogen lamps

#### **Product features**



- LED alternative to high voltage halogen lamps
- High color consistency: ≤ 6 SDCM
- Not dimmable
- Base: E27
- Lamp made of glass
- Good quality of light; color rendering index CRI ≥ 80
- Lifetime up to 15,000 h
- Type of protection: IP65

# TECHNICAL DATA

# Electrical data

Nominal wattage	12 W
Construction wattage	12.00 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	120 W
Nominal current	90 mA
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Power factor $\lambda$	> 0.50

#### Photometrical data

Luminous intensity	2600 cd
Luminous flux	1035 lm
Nominal useful luminous flux 90°	1035 lm
Luminous efficacy	86 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Daylight
Color temperature	6500 K
Color rendering index Ra	≥80
Light color	865
Standard deviation of color matching	≤6 sdcm
Rated peak intensity	2600 cd

# Light technical data

Beam angle	30 °
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	134.00 mm
Diameter	122.00 mm
Maximum diameter	122 mm
Product weight	320.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

#### Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70

# Additional product data

Base (standard designation)	E27
Mercury content	0.0 mg
Mercury-free	Yes

### Capabilities

Dimmable	No

#### Certificates & Standards

Type of protection	IP65
Photobiological safety group acc. to EN62778	RG1

#### Country-specific categorizations

Order reference	LVPAR3812030 12
Craci relevance	

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E27
Length	134.00 mm
Height	122.00 mm
Width	122.00 mm

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075778269	Folding box 2	202 mm x 127 mm x 155 mm	746.00 g	3.98 dm <sup>3</sup>
4058075778276	Shipping box 12	421 mm x 398 mm x 183 mm	5205.00 g	30.66 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.