

# PRODUCT DATASHEET P CLAS P 15 1.5 W/2700 K E27

PARATHOM® CLASSIC P | LED lamps, classic mini-ball shape



#### Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor use in suitable outdoor luminaires only

### Product benefits

- Lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Lower energy consumption than incandescent or halogen lamps
- $\,-\,$  No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs

## Product features

- Professional LED lamps for line voltage
- Beam angle: up to 300°
- Not dimmable
- Lifetime up to 15,000 h





- Lamp made of glass
- Good quality of light; color rendering index  $R_{a:} \ge 80$ ; constant chromaticity

# TECHNICAL DATA

# Electrical data

Nominal wattage	1.5 W
Construction wattage	1.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	15 W
Nominal current	12 mA
Type of current	AC
Inrush current	1.57 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	416
Max. lamp number on MCB B16 A	666
Power factor $\lambda$	> 0.40

## Photometrical data

Luminous flux	136 lm
Nominal useful luminous flux 90°	136 lm
Luminous efficacy	90 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	77.00 mm
Diameter	45,0 mm
Maximum diameter	45 mm

Product weight	20.00 g	
Temperatures & operating conditions		
Ambient temperature range	-20+40 °C	
Maximum temperature at to test point	47 °C	
Lifespan		
Number of switching cycles	100000	
Lumen maintenance at end of service lifetime	0.70	
Rated lamp survival factor at 6,000 h ≥ 0.90		
Additional product data		
Base (standard designation)	E27	
Mercury content	0.0 mg	
Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the comple production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	
Capabilities		
Dimmable	No	
Certificates & Standards		
Energy efficiency class	F 1)	
Energy consumption	2.00 kWh/1000h	
Type of protection	IP20	
Standards	CE	
Photobiological safety group acc. to EN62778	RG0	
1) Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)	fficiency)	
Country-specific categorizations		
Order reference	LEDPCLP15 1,5W/	
Energy labelling regulation data acc EU 2019/2015		
	F07	
Light source cap-type (or other electric interface)	E27	

77.00 mm

Length

Height	45,0 mm
Width	45,0 mm
EPREL ID	1402956
Model number	AC17470

# LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075287945	Folding box	46 mm x 46 mm x 93 mm	30.00 g	0.20 dm <sup>3</sup>
4058075287952	Shipping box 10	240 mm x 101 mm x 108 mm	321.00 g	2.62 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.