

# PRODUCT DATASHEET LED PIN 30 300° P 2.6W 840 Clear G9

PARATHOM® LED PIN G9 | LED lamps with retrofit pin base G9



#### Areas of application

- Atmospheric accent lighting throughout the home
- Shops, hotels and restaurants
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Good all-around light emission
- Long lifetime of up to 15,000 h
- Four year guarantee
- Lower energy consumption than incandescent or halogen lamps

#### Product features

- LED alternative to conventional high voltage lamps
- Good quality of light; color rendering index R<sub>a</sub>: ≥ 80; constant chromaticity






## TECHNICAL DATA

## Electrical data

Nominal wattage	2.6 W
Construction wattage	2.60 W
Nominal voltage	220240 V
Operating mode	AC Mains
Claimed equiv. conventional lamp power	30 W
Nominal current	23 mA
Type of current	AC
Inrush current	3.06 A
Operating frequency	50/60 Hz
Mains frequency	50/60 Hz
Max. lamp number on MCB B10 A	41
Max. lamp number on MCB B16 A	52
Total harmonic distortion	< 170 %
Power factor $\lambda$	> 0.40

## Photometrical data

Luminous flux	320 lm
Nominal useful luminous flux 90°	320 lm
Luminous efficacy	123 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Cool White
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.4



349924\_4000K\_Se\_5630.eps

# Light technical data

Beam angle	300 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight

Overall length	47.00 mm
Diameter	15.00 mm
Maximum diameter	15 mm
Product weight	6.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	72 °C

# Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	G9
Mercury content	0.0 mg
Design / version	Clear

## Capabilities

Dimmable	No

#### Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	3.00 kWh/1000h
Type of protection	IP20
Standards	CE / EAC
Photobiological safety group acc. to EN62778	RG1

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Country-specific categorizations

Temperature range at storage

Order reference	LEDPPIN30 CL 2,
LOGISTICAL DATA	

-20...+80 °C

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	G9
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.00
Claim of equivalent power	Yes
Length	47.00 mm
Height	15.00 mm
Width	15.00 mm

Chromaticity coordinate x	0.382
Chromaticity coordinate y	0.380
R9 Colour rendering index	1
Beam angle correspondence	SPHERE_360
Survival factor	0.90
LED light source replaces a fluorescent light source	No
EPREL ID	522876
Model number	AC32092

#### Safety advice

- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.

#### **DOWNLOAD DATA**

	Documents and certificates	Document name
PDF	Declarations of conformity	LED PIN 40 NON DIM G9

Photometric and lighting design files Document name	
Spectral power distribution	349924_4000K_Se_5630.eps

#### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075626010	Folding box 1	28 mm x 28 mm x 67 mm	10.00 g	0.05 dm <sup>3</sup>
4058075626027	Shipping box 20	150 mm x 122 mm x 77 mm	236.00 g	1.41 dm <sup>3</sup>
4058075626034	Shipping box 120	256 mm x 160 mm x 248 mm	1551.00 g	10.16 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.