

PRODUCT DATASHEET

HQI HIGHBAY 250 120 ° 95 W/4000 K E40

HQI LED HIGHBAY | LED replacement for HID lamps for high-bay luminaires



Areas of application

- LED alternative for applications requiring a high luminous flux
- Industrial and storage facilities
- Outdoor applications only in suitable luminaires

Product benefits

- Direct replacement for traditional HQI and NAV lamps thanks to CCG and ignitor compatibility
- Energy savings of up to 68 % when replacing traditional HQI lamps
- Effective thermal management for wide operating temperature range
- Low maintenance costs thanks to long lifetime
- Instant 100 % light, no warm-up time

Product features

- Type of protection: IP40
- High surge protection: up to 4 kV (L-N)




TECHNICAL DATA**Electrical data**

| | |
|--|--|
| Nominal wattage | 95 W |
| Construction wattage | 95.00 W |
| Nominal voltage | 110 V |
| Operating mode | Conventional control gear (CCG), Conventional control gear (CCG) and ignitor |
| Claimed equiv. conventional lamp power | 250 W |
| Nominal current | 2300 mA |
| Type of current | AC |
| Inrush current | ≤75 A |
| Operating frequency | 50 Hz |
| Mains frequency | 50 Hz |
| Max. lamp number on MCB B10 A | 15 |
| Max. lamp number on MCB B16 A | 24 |
| Total harmonic distortion | < 80 % |
| Power factor λ | 0.70 |

Photometrical data

| | |
|---|------------|
| Luminous flux | 13000 lm |
| Nominal useful luminous flux 90° | 13000 lm |
| Luminous efficacy | 136 lm/W |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Cool White |
| Color temperature | 4000 K |
| Color rendering index Ra | ≥80 |
| Light color | 840 |
| Standard deviation of color matching | ≤6 sdcn |
| Rated LLMF at 6,000 h | 0.80 |




EPREL data spectral diagram PROF LEDr 4000K

Light technical data

| | |
|---------------------|----------|
| Beam angle | 120 ° |
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & Weight



| | |
|------------------|-----------|
| Overall length | 310.00 mm |
| Diameter | 230.00 mm |
| Maximum diameter | 230 mm |
| Product weight | 1100.00 g |

Temperatures & operating conditions

| | |
|--------------------------------------|--------------|
| Ambient temperature range | -20...+50 °C |
| Maximum temperature at tc test point | 65 °C |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 50000 h |
| Number of switching cycles | 100000 |

| | |
|--|--------|
| Lumen maintenance at end of service lifetime | 0.70 |
| Rated lamp survival factor at 6,000 h | ≥ 0.90 |

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | E40 |
| Mercury content | 0.0 mg |

Capabilities

| | |
|----------|----|
| Dimmable | No |
|----------|----|

Certificates & Standards

| | |
|--|------------------|
| Energy efficiency class | E |
| Energy consumption | 105.00 kWh/1000h |
| Type of protection | IP40 |
| Standards | CE |
| Photobiological safety group acc. to EN62778 | RG1 |

Country-specific categorizations

| | |
|-----------------|-----------------|
| Order reference | HQILEDH13000 95 |
|-----------------|-----------------|

Energy labelling regulation data acc EU 2019/2015



| | |
|---|--------------|
| Lighting technology used | LED |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | E40 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 310.00 mm |
| Height | 230.00 mm |
| Width | 230.00 mm |
| Chromaticity coordinate x | 0.381 |
| Chromaticity coordinate y | 0.379 |

| | |
|--|------------|
| Beam angle correspondence | SPHERE_360 |
| Survival factor | 0.90 |
| Displacement factor | 0.70 |
| LED light source replaces a fluorescent light source | No |
| EPREL ID | 567215 |
| Model number | AC35215 |

Safety advice

- The bulb may be larger and heavier than the replaced bulb. Before installation it must be checked, if the luminaire and especially the holder is capable of carrying the weight of the lamp.
- Safety sling has to be installed.
- To ensure full light efficiency and product lifetime, it is recommended to detach any glass or cover of the luminaire.
- Only suitable for temperatures of up to 50 °C inside of the luminaire.
- Not suitable for operation with 230 V line voltage or electronic control gear.

DOWNLOAD DATA

| Documents and certificates | | Document name |
|---|--|---|
|  | User instruction / safety instructions | HQI LED Highbay |
| Photometric and lighting design files | | Document name |
|  | Spectral power distribution | EPREL data spectral diagram PROF LEDr 4000K |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075612631 | Folding box 1 | 247 mm x 247 mm x 333 mm | 1321.00 g | 20.32 dm ³ |
| 4058075612648 | Shipping box 4 | 515 mm x 515 mm x 355 mm | 5961.00 g | 94.15 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.