

# PRODUCT DATASHEET ST CLAS P 60 FR 7.5 W/2700 K E14

LED STAR CLASSIC P | LED lamps, classic mini-ball shape



#### Areas of application

- Domestic applications
- General illumination
- Atmospheric accent lighting throughout the home
- Outdoor use in suitable outdoor luminaires only

#### Product benefits

- Lower energy consumption than incandescent or halogen lamps
- Easy replacement of classic lamps thanks to compact design
- Instant 100 % light, no warm-up time

#### **Product features**

- LED alternative to conventional lamps
- Mercury-free lamps





## TECHNICAL DATA

## Electrical data

Nominal wattage	7.5 W
Construction wattage	7.50 W
Nominal voltage	220240 V
Claimed equiv. conventional lamp power	60 W
Nominal current	58 mA
Type of current	AC
Inrush current	4.09 A
Operating frequency	5060 Hz
Mains frequency	5060 Hz
Max. lamp number on MCB B10 A	287
Max. lamp number on MCB B16 A	461
Power factor λ	> 0.50


#### Photometrical data

Luminous flux	806 lm
Nominal useful luminous flux 90°	806 lm
Luminous efficacy	107 lm/W
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Color temperature	2700 K
Color rendering index Ra	≥80
Light color	827
Standard deviation of color matching	≤6 sdcm
Rated LLMF at 6,000 h	0.80

# Light technical data

Beam angle	200 °
Warm-up time (60 %)	< 0.50 s
Starting time	< 0.5 s

# Dimensions & Weight



Overall length	90.00 mm
Diameter	47.00 mm
Maximum diameter	47 mm
Product weight	26.00 g

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Maximum temperature at tc test point	85 °C

## Lifespan

Number of switching cycles	100000
Lumen maintenance at end of service lifetime	0.70
Rated lamp survival factor at 6,000 h	≥ 0.90

# Additional product data

Base (standard designation)	E14
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Frosted
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

# Capabilities

Dimmable	No
----------	----

#### Certificates & Standards

Energy efficiency class	F 1)
Energy consumption	8.00 kWh/1000h
Type of protection	IP20
Standards	CE
Photobiological safety group acc. to EN62778	RG0

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A++ (highest efficiency) to E (lowest efficiency)

#### Country-specific categorizations

Order reference	LEDSCLESO 7.5W/
Order reference	LEDSCLP60 7,5W/

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	E14
Correlated colour temperature type	SINGLE_VALUE
Length	90.00 mm
Height	47.00 mm
Width	47.00 mm
EPREL ID	1403245
Model number	AC24733

#### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075127470	Blister 1	45 mm x 140 mm x 120 mm	37.00 g	0.76 dm <sup>3</sup>
4058075127487	Shipping box	297 mm x 150 mm x 130 mm	374.00 g	5.79 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

- For further products and actual information concerning LED lamps see www.ledvance.com/ledlamps
- For Guarantee see www.ledvance.com/guarantee

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.